Empatia Wall/Ceiling


Technical data

















	EMPATIA 16	EMPATIA 26	EMPATIA 36
MATERIALS	Base in painted white die-cast aluminum.	Base in painted white die-cast aluminum.	Base in painted white die-cast aluminum.
	Diffuser in handblown glass, clear towards the bottom and frosted at the top to allow reflection of the light without glaring and without losing efficiency.	Diffuser in handblown glass, clear towards the bottom and frosted at the top to allow reflection of the light without glaring and without losing efficiency.	Diffuser in handblown glass, clear towards the bottom and frosted at the top to allow reflection of the light without glaring and without losing efficiency.
	Light pipe in transparent low absorption coefficient methacrylate guides the light to the diffuser.	Light pipe in transparent low absorption coefficient methacrylate guides the light to the diffuser.	Light pipe in transparent low absorption coefficient methacrylate guides the light to the diffuser.
EMISSION	Diffused	Diffused	Diffused
LIGHT SOURCE	LED 11W 3000K>80CRI	LED 16W 3000K>80CRI	LED 24W 3000K>80CRI
DIMMING FEATURE	Non dimmable	Non dimmable	Non dimmable
DELIVERED LUMENS	530lm	710lm	1189lm
FINISH	○ Clear & Frosted (Diffuser) ○ White (Base)	○ Clear & Frosted (Diffuser) ○ White (Base)	○ Clear & Frosted (Diffuser) ○ White (Base)
CERTIFICATIONS	c.UL.us listed, IP20	c.UL.us listed, IP20	c.UL.us listed, IP20