


Mercury Suspension



13³/₄"
35 cm


22³/₈"
56.9 cm

Standard length

Min. 37¹⁵/₁₆" - Max. 102¹⁵/₁₆"
Min. 96.4 cm - Max. 261.4 cm

Extended length

Min. 37¹⁵/₁₆" - Max. 215³/₄"
Min. 96.4 cm - Max. 548 cm



ø 27⁹/₁₆"
ø 70 cm

MINI LED

MATERIALS

Lighting units in die-cast aluminum.
Reflective units made of injection-molded thermoplastic.
Material with metallic finish. Reflector in stainless steel.

EMISSION

Indirect

LIGHT SOURCE

LED 29W 3000K >93CRI
or
LED 29W 2700K >93CRI

DIMMING FEATURE

Dimmable


FINISH

● Stainless steel

CERTIFICATIONS

c.UL.us listed

Technical Data



19¹¹/₁₆"
50 cm


24⁷/₁₆"
62 cm

Standard length

Min. 44¹/₁₆" - Max. 103¹/₈"
Min. 112 cm - Max. 262 cm

Extended length

Min. 44¹/₁₆" - Max. 215³/₄"
Min. 112 cm - Max. 548 cm



ø 43⁵/₁₆"
ø 110 cm

LED

MATERIALS

Lighting units in die-cast aluminum.
Reflective units made of injection-molded thermoplastic.
Material with metallic finish. Reflector in stainless steel.

EMISSION

Indirect

LIGHT SOURCE

LED 58W 3000K >93CRI
or
LED 58W 2700K >93CRI

DIMMING FEATURE

Dimmable

FINISH

● Stainless steel

CERTIFICATIONS

c.UL.us listed

