

Raingler

NETS & GRIPS

1954 – Newer Jeep Wrangler Upper Half Rear Barrier Divider Net Install

NOTE: Many newer models have B-pillar handles and even overhead on the ceiling that can be used for some of the top mounting locations. Check to see if you prefer to use these factory locations as the nets typically have enough adjustment to allow for this option. If your vehicle does not have handles in desired locations or you prefer to install mounting points for better fitment, please follow the below steps.

IMPORTANT: READ INSTRUCTIONS FULLY BEFORE STARTING

Time: About 20 minutes



Paw Level:

1. **Tools:** Ratchet Wrench with Extension
2. Panel Removal Tool
3. Torx T-45



Step 1

Inspect the netting before you begin the install. Any shipping damage must be reported to carrier and us immediately.

Step 2

Fold down the back seats and hold the net so that the base of the trapezoid shape is towards the floor about even with the body top lip. The label faces to the front of the Jeep.

Step 3

Note: The lower straps will hook onto the Torx bolt and black anchor plate on the inside of the door catch.

Pull back the front upper piece of interior carpet so you can access the inside back plate of the door catch Torx bolts go into.

Step 4

Loosen the top Torx and remove. Loosen the lower Torx enough so that the inside nutsert plate can flex apart enough to place the black anchor plate between the nutsert plate and the inner body support bracket.



Step 5

Insert the black anchor plate oriented up as shown. Tighten the Torx bolts back in with the upper Torx bolt going through the black anchor plate's holes. Pay attention that the door catch plate is reinstalled into the original position. You can see the lines easy as you tighten it down.

IMPORTANT, the rear seat belt strap must run over and in front of these net straps. Remember to leave these straps loose until the very end of the install.



Raingler
NETS & GRIPS

Step 6

The middle straps anchor to our side net windows to create a three-piece divider. If you do not plan to add these, the middle straps can be simply removed or wrapped up as shown in our video on the Vimeo Channel to allow for future options.



Step 7

The upper straps wrap around the roll bar and then center it all up tightening the upper two, then the middle two and then fold the back seats into place and then the lower two making sure they allow the rear seat to fully seat and catch. Snug and center any more needed.

Step 8

Wrap the excess strap ends thru the buckle slit and around the web a few times and under itself and then pull snug to not allow any end to be loose and to also slow down any would be hands that might want to get something out of the back.

See video here for details:
<https://vimeo.com/316588617>



Thank you for purchasing Raingler Nets.
If you have any questions please contact us,
we are here to help!

Check out the video here:
<https://vimeo.com/raingler>

Raingler
NETS & GRIPS