Brewing Water 850 GPD Reverse Osmosis System Specification Sheet

Craft Brew 850 62 Stacker is a compact unit designed to provide productivity, automatic operation and low maintenance. The 850 sits on top of a 62 gallon pressure tank with 40 gallons of draw down of Reverse Osmosis Water. The 850 comes per-plumbed and ready to install, the system come with all the options that is expected with Craft Brew Reverse Osmosis Systems, Blending valve, TSD Meter and UV. The 850 is fully automated sustem.



Standard Features

Controller: Integrated Aquatrol controller provides automatic operation for optinum performance.

- Low Pressure Switch
- Contactor
- Level Switch
- Manual -automatic selector switch
- TDS sensor to monitor the water quality

Membrane Housing: 4" x 21" Stainless Steel

RO Membrane: (1) 4" x 21"

Pump: Brass Rotary vane type (coupled to 1725 RPM motor)

incoming Solenoid Valve: Brass 120v 3/8" Flow Meter: Panel Mount 0.1-1 GPM

Pressure Gauges: 100 & 300 psi Glycerin filled

Waste and Recycle Valve: 316 Stainless Steel Needle Valve

Filter Housings: (3) NSF 10"

62 Gallon Tank with 40 gallon draw down.

Pre-filters:

-(1) 2.5" x 10" Polyspun 5 Micron Sediment

-(1) 2.5" x 10" 5 Micron Catalytic Carbon Block

Post filter (1) 2.5" x 10" 5 Micron Catalytic Carbon Block

Frame: Electrostatic Powder Coated

Installation Kit



Specifications

Production: 850 GPD* Membrane: 4" x 21" (1)

Operating Pressure: 100-150 psi Capacity Rotary Pump: 100 gph System Dimension: 26" x 73" x 23"

Weight: 70lbs

Electrical Power Supply: 120V/60 Hz



