



## Craft Brew 850 Reverse Osmosis Brewing System

1336 Moorpark Rd Suite 239  
Thousand Oaks, Ca 91360  
p. 805-777-7037 f. 800-359-6895  
email: support@cbw.beer

Craft Brew 850 GPD is a compact unit designed to productivity, automatic operation and low maintenance. The 850 comes loaded with options that are standard on all Craft Brew Reverse Osmosis Brewing Systems. Blending valve to control your incoming brewing water, pressure switch or float switch controlled, waste recycle stainless steel needle valve and the final stage UV protection.

### Standard Features

Controller: integrated Aquatroll controller provides automatic operation for optimal performance

- . Low pressure switch
- . Contactor
- . Level switch
- . Manual-automatic selector switch
- . TDS sensor to monitor the water quality

Membrane Housing: 4" x 21" stainless steel

RO Membrane: (1) 4" x 21"

Pump: Brass Rotary Vane Type (coupled to a 1725 RPM motor)

Incoming solenoid valve: Brass 120 V 3/8"

Flow Meter: 0.1-1 GPM

Pressure Gauges: 100 & 300 psi glycerin filled

Waste and Recycle valves: 316 stainless steel needle valves

Filter Housings: (3) NSF 2.5" x 10"

Pre-Filters:

- . (1) 2.5" x 10" polyspun 5 µm sediment filter
- . (1) 2.5" x 10" 5 µm carbon block

Post Filter:

- . (1) 2.5" x 10" 5 µm carbon block

Frame: Electrostatic Powder Coated

Installation kit



### Specifications

Production: 850 GPD

Operating Pressure: 100-150 psi

Capacity Rotary Pump: 100 gpH

System Dimensions: 26" x 23" x 20"

Weight: 70lbs

Electrical Power Supply: 120v/60 Hz

