39214-101 Issue 5A

MINIDISC REMOTE INDICATOR PART No. 53832-070/072


THE REMOTE INDICATOR IS POLARITY SENSITIVE CONNECT POSITIVE LINE TO TERMINAL A OR B AND NEGATIVE LINE TO TERMINAL C.

CONNECTIONS

DETECTOR RANGE SERIES 60 SERIES 60 INTRINSICALLY SAFE XP95 INTRINSICALLY SAFE DISCOVERY ALARMSENSE 5 - 36V

VOLTAGE, A & C MAX CURRENT, B & C OPERATING TEMPERATURE

MINIDISC REMOTE INDICATOR PART No. 53832-070/072



DETECTOR RANGE CONNECTIONS SERIES 60 SERIES 60 INTRINSICALLY SAFE XP95 INTRINSICALLY SAFE ALARMSENSE ORBIS VOLTAGE, A & C 5 - 36V MAX CURRENT, B & C 25mA, UP TO 40°C OPERATING TEMPERATURE -10° TO +60°C

MINIDISC REMOTE INDICATOR PART No. 53832-070/072

THE REMOTE INDICATOR IS POLARITY SENSITIVE CONNECT POSITIVE LINE TO TERMINAL A OR B AND NEGATIVE LINE TO TERMINAL C.

DETECTOR RANGE	CONNECTIONS
SERIES 60	A & C
SERIES 60 INTRINSICALLY SAFE	A & C
XP95	A & C
XP95 INTRINSICALLY SAFE DISCOVERY	B & C A & C
ALARMSENSE	B & C
ORBIS	A & C
VOLTAGE, A & C	5 - 36V
MAX CURRENT, B & C	25mA, UP TO 40°C
OPERATING TEMPERATURE	−10° TO +60°C

MINIDISC REMOTE INDICATOR PART No. 53832-070/072

THE REMOTE INDICATOR IS POLARITY SENSITIVE CONNECT POSITIVE LINE TO TERMINAL A OR B AND NEGATIVE LINE TO TERMINAL C.

DETECTOR RANGE CONNECTIONS SERIES 60 SERIES 60 INTRINSICALLY SAFE XP95 INTRINSICALLY SAFE DISCOVERY ALARMSENSE VOLTAGE, A & C 5 - 36V MAX CURRENT, B & C 25mA, UP TO 40°C OPERATING TEMPERATURE -10° TO +60°C

39214-101 Issue 5A

25mA, UP TO 40°C

-10° TO +60°C

THE REMOTE INDICATOR IS POLARITY SENSITIVE

CONNECT POSITIVE LINE TO TERMINAL A OR B


AND NEGATIVE LINE TO TERMINAL C.

39214-101 Issue 5A

MINIDISC REMOTE INDICATOR PART No. 53832-070/072

MINIDISC REMOTE INDICATOR

PART No. 53832-070/072



DETECTOR RANGE CONNECTIONS SERIES 60 INTRINSICALLY SAFE XP95 INTRINSICALLY SAFE DISCOVERY ALARMSENSE ORBIS VOLTAGE, A & C 5 - 36V MAX CURRENT, B & C -10° TO +60°C



MINIDISC REMOTE INDICATOR

PART No. 53832-070/072

THE REMOTE INDICATOR IS POLARITY SENSITIVE CONNECT POSITIVE LINE TO TERMINAL A OR B AND NEGATIVE LINE TO TERMINAL C.

MINIDISC REMOTE INDICATOR

PART No. 53832-070/072

THE REMOTE INDICATOR IS POLARITY SENSITIVE CONNECT POSITIVE LINE TO TERMINAL A OR B AND NEGATIVE LINE TO TERMINAL C.

DETECTOR RANGE CONNECTIONS SERIES 60 INTRINSICALLY SAFE XP95 INTRINSICALLY SAFE DISCOVERY ALARMSENSE ORBIS VOLTAGE, A & C MAX CURRENT, B & C 25mA, UP TO 40°C OPERATING TEMPERATURE -10° TO +60°C

SERIES 60 INTRINSICALLY SAFE XP95 INTRINSICALLY SAFE DISCOVERY ALARMSENSE ORBIS VOLTAGE, A & C

MAX CURRENT, B & C

OPERATING TEMPERATURE

DETECTOR RANGE

CONNECTIONS

5 - 36V 25mA, UP TO 40°C -10° TO +60°C

OPERATING TEMPERATURE

25mA, UP TO 40°C

39214-101 Issue 5A

DETECTOR RANGE CONNECTIONS SERIES 60 INTRINSICALLY SAFE XP95 INTRINSICALLY SAFE DISCOVERY ALARMSENSE ORRIS VOLTAGE, A & C 5 - 36V MAX CURRENT, B & C

OPERATING TEMPERATURE

25mA, UP TO 40°C -10° TO +60°C