

## Four-Post Service Lift Comparison (12K & 14K)

Model Number	FP12K-K	FP14K	FP14KA	FP14KC-X	FP14KAC-X	FP14KO -A
CAPACITY (LBS)	12,000	14,000	14,000	14,000	14,000	14,000
LIFT CONFIGURATION	4-POST/SERVICE	4-POST/SERVICE	4-POST/ALIGNMENT	4-POST/ALIGNMENT	4-POST/ALIGNMENT	4-POST/ALIGNMENT
CEILING HEIGHT MINIMUM	10'	10'	10'	10'	10'	10'
OVERALL (POST) HEIGHT	87.6" (7'3")	85" (7'1")	85" (7'1")	92-1/2" (7' 8-1/2")	92-1/2" (7' 8-1/2")	92" (FRONT) & 86" (REAR)
OVERALL LENGTH (W/RAMPS)	232-1/2" (19' 4-1/2")	237" (19' 11")	237" (19' 11")	252-1/2" (21'-1/2")	252-1/2" (21'-1/2")	291" (24' 5")
OVERALL LENGTH (W/O RAMPS)	202-1/2" (16' 10-1/2")	207" (17' 4")	207" (17' 4")	208-1/2" (17' 1-1/2")	208-1/2" (17' 1-1/2")	249" (20' 9")
OVERALL WIDTH	123" (10' 3")	123" (10' 3")	123" (10' 3")	142" (11' 10")	142" (11' 10")	139" (11' 7")
MAX CLEARANCE (UNDER TRACKS)	63-1/4" (5' 3-1/4")	60" (5')	60" (5')	69-5/8" (5' 9-5/8")	69-5/8" (5' 9-5/8")	64" (5' 4")
LIFTING HEIGHT	67-1/2" (5' 7-1/2")	65-1/4" (5' 5-1/4")	67" (5' 7")	77.5" (6' 5-1/2")	79.5" (6' 7-1/2")	73 (6' 1")
WIDTH BETWEEN POSTS	105" (8'9")	108" (9')	108" (9')	116.25" (9' 8-1/4")	116.25" (9' 8-1/4")	117" / 118" (9' 9")
RAMP LENGTH	30"	30"	30"	44"	44"	42"
RAMP WIDTH	19-1/4"	20-1/4"	20-1/4"	20-1/4"	20-1/4"	19"
SAFETY LOCK	SINGLE POINT (MANUAL)	SINGLE POINT (PNEUMATIC)	SINGLE POINT (PNEUMATIC)	SINGLE POINT (PNEUMATIC)	SINGLE POINT (PNEUMATIC)	SINGLE POINT (PNEUMATIC)
MAX WHEEL BASE (2-WHEEL)	176" (14' 8")	192" (16')	164" (13' 8")	N/A	166.75" (13' 10-3/4")	208" (17' 4")
MAX WHEEL BASE (4-WHEEL)	N/A	N/A	89" / 150"	N/A	103" / 157"	82" / 158"
POWER PACK (HP/PH-V-A)	1HP/1PH-220V-20A	1HP/1PH-220V-20A	1HP/1PH-220V-20A	1HP/1PH-220V-20A	1HP/1PH-220V-20A	1HP/1PH-220V-20A
CABLE DIAMETER	7/16"	N/A (CHAIN)	N/A (CHAIN)	7/16"	7/16"	7/16"
SHIPPING WEIGHT (LBS)	2255	2615	3240	2690	3810	4160
<i>Optional BRIDGE JACK</i>	RJ-7K or RJ-8K	RJ-7K or RJ-8K	RJ-7K or RJ-8K	RJ-7K or RJ-8K	RJ-7K or RJ-8K	RJ-7K or RJ-8K
CONCRETE SPEC	3000 PSI	4.25"	3.25" MIN. PENETRATION with 3/4" X 5.5" ANCHORS			
HYDRAULIC OIL	Non-Detergent / Non-Foaming Hydraulic Oil -- SAE10 / AW32					

