

## Four-Post Storage Lift Comparison (8K & 9K)

Model Number	FP8K-B	FP8K-DX	FP8K-DX-XLT	FP9K-DX-XLT
CAPACITY (LBS)	8,000	8,000	8,000	9,000
LIFT CONFIGURATION	4-POST/STORAGE	4-POST/STORAGE	4-POST/STORAGE	4-POST/STORAGE
CEILING HEIGHT MINIMUM	9'	9'	9'	10'
OVERALL (POST) HEIGHT	86" (7'2")	86" (7'2")	94" (7'10")	97" (8'1")
OVERAL LENGTH (W/RAMPS)	207-5/16" (17' 3-5/16")	207-5/16" (17' 3-5/16")	222-1/2" (18' 5-1/2")	239" (19' 11")
OVERAL LENGTH (W/O RAMPS)	170-5/16" (14' 2-5/16")	170-5/16" (14' 2-5/16")	185-1/2" (15' 5-1/2")	202 (16' 10")
OVERALL WIDTH	103-1/2" (8' 7-1/2")	103-1/2" (8' 7-1/2")	109-3.8" (9' 1-3/8")	123" (10' 1")
WIDTH BETWEEN POSTS	94-1/2" (7' 10-1/2")	94-1/2" (7' 10-1/2")	100-5/16" (8' 4-5/16")	111-1/2" (9' 3-1/2")
MAX CLEARANCE (UNDER TRACKS)	70" (5' 10")	70" (5' 10")	78" (6' 6")	81" (6' 11")
LIFTING HEIGHT	74-3/4" (6' 2-3/4")	74-3/4" (6' 2-3/4")	82-1/4" (6' 10-1/4")	85" (7' 1")
RAMP LENGTH	37"	37"	37"	37"
RAMP WIDTH	18-1/2"	18-1/2"	18-1/2"	20"
SAFETY LOCK POSTIONS	10	10	12	11
LOCK RELEASE	SINGLE POINT MANUAL	SINGLE POINT MANUAL	SINGLE POINT MANUAL	SINGLE POINT MANUAL
POWER PACK (HP/PH-V-A)	1HP/1PH-115V-20A	1HP/1PH-115V-20A	1HP/1PH-115V-20A	1HP/1PH-115V-20A
CABLE DIAMETER	3/8"	3/8"	3/8"	3/8"
DRIP TRAYS (INCLUDED)	NO	YES	YES	YES
CASTER (MOBILE)	NO	YES	YES	YES
SHIPPING WEIGHT (LBS)	1545	1705	1800	2354
<i>Optional BRIDGE JACK</i>	SJ-35	SJ-35	SJ-35	RJ-45
CONCRETE SPEC	3000 PSI	4.25"	3.25" MIN. PENETRATION with 3/4" X 5.5" ANCHORS	
HYDRAULIC OIL	Non-Detergent / Non-Foaming Hydraulic Oil -- SAE10 / AW32			

