

Two-Post Lift Comparison (12K - 15K)

Model Number	TP12KC-D	TP12KSC-DX (ALI/ETL Certified)	TP12KFX (LTP-12FX)	TP15KAC
CAPACITY	12,000 LBS	12,000 LBS	12,000 LBS	15,000 LBS
LIFT CONFIGURATION	OVERHEAD	OVERHEAD	FLOOR PLATE	OVERHEAD
CEILING HEIGHT MINIMUM	14'	14'3"	10'6"	15'
HEIGHT OVERALL	165" (13'9")	168-1/2" (14'-12")	121-1/2" (9'11'-12")	179.5" (14'11")
LIFTING HEIGHT	72" (6')	75" (6'3")	76.5" (6'4'-12")	76.5" (6'4'-12")
LIFTING HEIGHT (W/ADAPTERS)	79 5/8" (6'7.5")	79 5/8" (6'7.5")	80" (6'8")	87" (6'11")
LOW PAD HEIGHT	5.5"	4-7/8"	9"	9"
WIDTH OVERALL (w/Pump)	151.125" (12'7'-18")	151-5/16" (12'-7-5/16")	147-7/8" (12'3-7/8")	148-3/8" (12' 4-3/8")
WIDTH OVERALL (w/o Pump)	140.5" (12'8'-12")	140.5" (12'8'-12")	137-1/4" (11'5'-14")	138" (11' 6")
WIDTH BETWEEN COLUMNS	122" (10'2")	122" (10'2")	120" (10')	120-3/4" (10'3/4")
TIRE/DRIVE-THRU WIDTH	109" (9'1")	109" (9'1")	107" (8'11")	108" (9')
ARM ATRICULATION	SYMMETRIC	SYMMETRIC	SYMMETRIC	SYMMETRIC
FRONT ARM REACH (MIN/MAX)	37.5" - 57"	37.5" - 57"	37" - 52"	37" - 52"
REAR ARM REACH (MIN/MAX)	37.5" - 57"	37.5" - 57"	37" - 52"	37" - 52"
ADAPTERS (2 SETS OF 4 INCLUDED)	3" AND 5"	2.6" AND 5"	3" AND 5"	3" AND 5"
MAX. LOAD PER ARM (LBS)	3000	3000	3000	3750
SAFETY LOCKING SYSTEM	SINGLE POINT	SINGLE POINT	DUAL POINT	SINGLE POINT
POWER PACK (HP-V-A)	2HP/1PH-220V-20A	2HP/1PH-220V-20A	2HP/1PH-220V-20A	2HP/1PH-220V-20A
CABLE DIAMETER	3/8"	DIRECT DRIVE	3/8"	3/8"
LIFTING SPEED (SECONDS)	50	50	50	50
SHIPPING WEIGHT (LBS)	2235	2295	2460	2474

CONCRETE SPEC	3000 PSI / 4.25" THICKNESS / 3.25" MIN ANCHOR EMBEDDMENT / 3/4" X 5-1/2" ANCHORS / 7" MIN DISTANCE FROM ANY EDGE			
HYDRAULIC OIL	Non-Detergent / Non-Foaming Hydraulic Oil -- SAE10 / AW32			

Note: Big Foot: 34.5" x 20.5"

