

## Two-Post Lift Comparison (9K - 11K)

Model Number	TP9KFX (LTP-9F)	TP9KF-TUX	TP9KACX (LTP-9X)	TP9KAC-TUX	TP10KAC-DX (AL/IE TL Certified)	TP11KACX (LTP-11DX)
CAPACITY	9,000 LBS.	9000 LBS	9000 LBS	9000 LBS	10,000 LBS	11,000 LBS
LIFT CONFIGURATION	FLOOR PLATE	FLOOR PLATE	OVERHEAD	OVERHEAD	OVERHEAD	OVERHEAD
CEILING HEIGHT MINIMUM	10'	10'	12'	12' 4"	12' 4"	12' 4"
HEIGHT OVERALL	111" (9' 4")	111.9" (9' 4")	142.9" (11' 11")	142.7" (11'10-5/8")	144" (12')	142.7" (11'10")
LIFTING HEIGHT	72" (6')	72" (6')	72" (6')	72" (6')	71" (5'11")	71" (5'11")
LIFTING HEIGHT (w/ADAPTERS)	75 1/2" (6'3-1/2")	75 1/2" (6'3-1/2")	75-7/8" (6'3-7/8")	75-7/8" (6'3-7/8")	74-7/8" (6'2-7/8")	76-1/2" (6'4-1/2")
LOW PAD HEIGHT	4 1/2"	4"	4"	4"	4"	4"
WIDTH OVERALL (w/Pump)	134.6" (11' 2-1/2")	134.6" (11' 2-1/2")	138" (11' 6")	134.6" (11' 2")	145-1/2" (12' 1-1/2")	145-1/2" (12' 1-1/2")
WIDTH OVERALL (w/o Pump)	121.6" (10' 1-1/2")	124" (10' 4")	128" (10' 8")	124" (10' 4")	135" (11' 3")	135" (11' 3")
WIDTH BETWEEN COLUMNS	110.4" (9' 2.4")	110.4" (9' 2.4")	113.6"	110.4" (9' 2.4")	116" (9'8")	116" (9'8")
TIRE/DRIVE-THRU WIDTH	101" (8' 4")	101" (8' 4")	96" (8')	93.7" (7'9")	104" (8'8")	104" (8'8")
ARM ARTICULATION	SYMMETRIC	SYMMETRIC	ASYMMETRIC	ASYMMETRIC	SYMMETRIC & ASYMMETRIC	SYMMETRIC & ASYMMETRIC
FRONT ARM REACH (MIN/MAX)	31" - 45"	31" - 45"	29" - 41"	28.5" - 41.4"	23" - 45"	23" - 45"
REAR ARM REACH (MIN/MAX)	31" - 45"	31" - 45"	37" - 57"	37" - 57"	41" - 59"	41" - 57"
ADAPTERS (2 SETS OF 4 INCLUDED)	1-3/8" AND 4"	1.3" AND 5"	1-3/8" AND 4"	1.3" AND 5"	2.6" AND 5"	2" AND 4"
MAX. LOAD PER ARM (LBS)	2250	2250	2250	2250	2500	2750
SAFETY LOCKING SYSTEM	DUAL POINT	DUAL POINT	DUAL POINT	DUAL POINT	SINGLE POINT	SINGLE POINT
POWER PACK (HP-V-A)	2HP/1PH-220V-20A	2HP/1PH-220V-20A	2HP/1PH-220V-20A	2HP/1PH-220V-20A	2HP/1PH-220V-20A	2HP/1PH-220V-20A
CABLE DIAMETER	3/8"	3/8"	3/8"	3/8"	DIRECT DRIVE	3/8"
LIFTING SPEED (SECONDS)	50	50	50	50	50	50
SHIPPING WEIGHT (LBS)	1500	1265	1370	1390	1705	1705

CONCRETE SPEC	3000 Psi	4.25"	3.25" ANCHOR EMBEDMENT & 7" DISTANCE FROM ANY EDGE			3/4" X 5-1/2" ANCHORS
HYDRAULIC OIL	Non-Detergent / Non-Foaming Hydraulic Oil -- SAE10 / AW32					

