

Scissor Lift Comparison

Model Number	7000 TLX	LR-26-PAD	MR6K-48X	MR6.5K-38
CAPACITY	7,000 LBS.	6000 LBS	6000 LBS	6500 LBS
LIFT CONFIGURATION	Scissor	Scissor	Scissor	Scissor
OVERALL LENGTH	51-1/3" (4'3-1/3")	86"	96-1/2" (8' 1/2")	77" (6' 5")
OVERALL WIDTH	64 3/8" (5' 4-3/8")	73"	39-5/8" - 62"	76-1/2" (6' 4-1/2")
WIDTH BETWEEN RUNWAYS	37-1/4" - 52-1/4"	35"	30"	33-1/4"
RUNWAY WIDTH	7-1/4"	19"	4.5"	18-3/16"
LIFTING HEIGHT	22-1/2"	26"	48"	38"
LIFTING HEIGHT (W/ADAPTERS)	23-1/2"	30"	54	39-1/2"
LOW PAD HEIGHT (DRIVE-OVER)	4-1/2"	3"	7"	4"
PADS LENGTH	31-1/2"	52"	24" - 83"	56"
ADAPTERS (2 SETS OF 4 INCLUDED)	-----	4"W x 6"L x 1-1/2" (RUBBER BLOCK) 4"W x 6"L x 3" (RUBBER BLOCK)	OPTIONAL	3" & 6"
LIFTING METHOD	MANUAL (HAND TOOL)	HYDRAULIC PUMP	HYDRAULIC PUMP	AIR/HYD (90-125 PSI)
POWER PACK (PH-V-A)	120V – 10 Amp (1/2")	1PH - 115V – 15 Amp	1PH - 115V – 15 Amp	1PH - 115V – 15 Amp
LIFTING SPEED (SECONDS)	30 - 40	35	40	40
SHIPPING WEIGHT (LBS)	214	955	945	1355
OPTIONS	-----	-----	-----	SUV ADAPTER (MR6K-38-SUV)

HYDRAULIC OIL Non-Detergent / Non-Foaming Hydraulic Oil -- SAE10 / AW32

