

Single-Post Lift Comparison

Model Number	SC-2K	MSC-6KLP	SP-6K-SS
CAPACITY	2,000 LBS.	6000 LBS	6000 LBS
LIFT CONFIGURATION	Single Column	Mobile Single Column	Single Post
CEILING HEIGHT MINIMUM	8'	9'	10'
HEIGHT OVERALL	84-1/2" (7' 1/2")	102-3/8" (8' 6-3/8")	110-1/4" (9' 2-1/4")
DEPTH / LENGTH	69-1/2" (5' 9-1/2")	101-9/16" (8' 5-9/16")	-----
OVERALL LENGTH (W/RAMPS)	-----	-----	188" (15' 8")
OVERALL WIDTH	64 5/8" (5' 4-5/8")	-----	112-3/16" (9' 4-3/16")
LIFTING HEIGHT	58" (4'10")	72" (6')	81-3/16" (6' 9-3/16")
LIFTING HEIGHT (W/ADAPTERS)	-----	74" / 76"	-----
LOW PAD HEIGHT (DRIVE-OVER)	2-3/4"	4"	4"
CLEARANCE UNDER TRACKS	4' 4"	6'6"	77-3/16" (6' 5-3/16")
RUNWAY LENGTH	-----	-----	152" (12' 8")
RUNWAY WIDTH	-----	-----	18-7/8"
BASE PLATE	-----	-----	52" x 39"
PLATFORM FRAME/STRUCTURE	64-1/2"W x 52-5/8"D	-----	-----
PLATFORM ALUMINUM DECK	36"W x 48"D	-----	-----
SWIVEL PAD HEIGHT (ADJUSTMENT)	-----	3-5/16" - 6-5/16")	-----
SCREW PADS	-----	Double Telescopic	-----
DISTANCE B/W LIFT PADS (OFF-SIDE)	-----	60" Max / 54" Min	-----
MAIN SIDE ARM REACH (TELESCOPIC)	-----	19-11/16" – 26"	-----
OFF-SIDE ARM REACH (TELESCOPIC)	-----	24-5/8" – 34"	-----
ADAPTERS (2 SETS OF 4 INCLUDED)	-----	2" AND 4"	-----
SAFETY LOCKING SYSTEM	Single Point (18)	Single Point (21)	Single Point (19)
POWER PACK (PH-V-A)	1PH-115V-20A	1PH-115V-15A	1PH-115V-20A
LIFT CHAIN / CABLE	Chain	Chain	3/8" (CABLE)
LIFTING SPEED (SECONDS)	90	-----	90
SHIPPING WEIGHT (LBS)	605	1850	2610
OPTIONS	Motor Cycle Vise (SC-2K-MVA)	UTV Kit / Cradle Adapters	DRIP TRAYS (FP-9KDX-DX)

CONCRETE SPEC (SC-2K & SP-6K-SS) 3000 PSI / 4.25" THICKNESS / 3.25" MIN ANCHOR EMBEDDMENT / 3/4" X 5-1/2" ANCHORS / 7" MIN DISTANCE FROM ANY EDGE

HYDRAULIC OIL Non-Detergent / Non-Foaming Hydraulic Oil -- SAE10 / AW32

