

Tire Changers - Comparison

Model Number	TC-400M (Motorcycle)	TC-430 (Economy)	TC-530	TC-950	TC-950 WPA (Left-Side Press Arm/Low Profile Tires)	TC-1300 (Tilt-Column / Leverless Design)
MAX. TIRE DIAMETER	37"	37-4/5"	38"	47"	47"	41"
MAX. TIRE WIDTH	10"	3" - 11"	3" - 12"	3" - 15"	3" - 15"	3" - 15"
RIM DIAMETER (INSIDE RIM CLAMP RANGE)	N/A	12" - 21"	12" - 23"	15" - 28"	15" - 28"	13" - 26"
RIM DIAMETER (OUTSIDE RIM CLAMP RANGE)	6" - 24"	10" - 18"	10" - 20"	13" - 24"	13" - 24"	11" - 24"
PNEUMATIC CLAMPS	4	4	4 (w/Inflation jets)	4 (w/Inflation jets)	4 (w/Inflation jets)	4 (w/Dual Inflation jets)
WORKING PRESSURE (PSI)	125	125	125	125	125	115 - 145
BEAD BREAKER (SIDE-MOUNTED) - KG	2,500	2,500	2,500	2,500	2,500	40,000
POWER SUPPLY	110V-15A-1PH	110V-15A-1PH	110V-15A-1PH	110V-15A-1PH / 1.5HP	110V-15A-1PH / 1.5HP	110V-15A-1PH / 1.5HP
LUBRICATOR	INCLUDED	INCLUDED	INCLUDED	INCLUDED	INCLUDED	INCLUDED
WATER SEPARATOR	INCLUDED	INCLUDED	INCLUDED	INCLUDED	INCLUDED	INCLUDED
AIR PRESSURE REGULATOR	INCLUDED	INCLUDED	INCLUDED	INCLUDED	INCLUDED	INCLUDED
MOUNT / DIS-MOUNT	MANUAL	MANUAL	MANUAL	SEMI-AUTOMATIC	SEMI-AUTOMATIC	SEMI-AUTOMATIC
NO RIM-MACHINE CONTACT (NO SCRATCH)	-----	-----	INCLUDED	INCLUDED	INCLUDED	-----
SHIPPING WEIGHT (LBS)	470	460	560	640	880	924

OPTIONAL FEATURES

MOTORCYCLE ADAPTERS (TC-MC-AN)	INCLUDED	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	-----
ADJUSTABLE TIRE SPREADER (TS-ATSB)	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
ASSIST PRESS ARM ASSEMBLY (TC-400M-B-PL230)	OPTIONAL	OPTIONAL	-----	-----	-----	-----
LEFT-SIDE PRESS ARM (TC-950-WPA-1)	-----	-----	-----	OPTIONAL	INCLUDED	-----



TC-MC-AN



TC-400M-B-PL230



TC-950-WPA-1



TS-ATSB

