



120 Valley Court  
Oak Ridge, TN 37830  
Ph: 865-482-5717  
FAX: 865-482-1281  
zypcoatings.com

## BN Glass Release Spray Special Instructions

**To avoid clogs and other issues, please follow these instructions.**

*BN Glass Release Spray is shipped with the squeeze-trigger sprayer separate from the bottle. This is to prevent clogging.*

### **How to Use and Clean Sprayer:**

1. Remove the cap from the bottle and connect the squeeze-trigger sprayer.  
**Save the cap.**
2. After using, remove the squeeze-trigger sprayer and replace the cap on the bottle.
3. Place the stem tube of the trigger sprayer into a container of water and spray until the liquid comes out clear. This keeps any residual paint from remaining in the squeeze-trigger sprayer – which can dry and clog the sprayer when used at a later time.

If the cleaning is not done and the sprayer clogs, try soaking the sprayer in water and then spraying until the liquid comes out clear. This will unclog the sprayer nozzle and allow uniform spraying once again.

### **How to Spray Molds:**

1. Always start with a clean sprayer.
2. **Shake vigorously** to re-suspend. There will be settling with this water-based product.
3. The coating can be varied by the frequency and strength of squeezing the trigger.
4. Spray lightly on the mold (preferably a preheated mold) and let soak-in and dry a bit (because it does apply a little thick).
5. Re-apply if there are bare spots.
6. The wet coating can be smoothed with small brush, if necessary.
7. Wait until the coating is dry to the touch and apply a second coat if desired.
8. Dry before using – at room temperature or with a dryer at 140 F (60 C) for about 30 minutes or with a conventional hair-dryer at “high heat” and “low fan speed” for a few minutes.

If desired, the sprayed mold can be heated up to around 300 F (150 C) to accelerate drying before firing or slumping. BN Glass Release is generally not recommended for stainless and metal molds or smooth or glazed surfaces, since the sprayer tends to give uneven coverage on those substrates. For those applications, try BN Aerosol Lubriccoat.

*Thank you for purchasing BN Glass Release Spray*