


## JUPITER JF2

GPS Embedded



### Product Description

The JF2 offers developers and integrators the smallest, completely integrated GPS solution for positioning applications based on a 1.8 V supply. It is fully interoperable with Telit cellular modules for a ready-to-use solution bundle with no additional integration effort or cost. The Telit cellular modules.

### Key Features

- Based on the SiRFstarIVTMCORE
- GNSS supported: GPS L1
- 11 x 11 x 2.6 mm QFN package
- Flash, EEPROM or ROM based versions
- Assisted GPS
- High RF sensitivity with jamming detection and removal
- Supply voltage range: 1.79 - 1.9 VDC
- Advanced power modes
- Ports: 1PPS, UART, I<sup>2</sup>C and SPI

### Key Benefits

- Supports AGPS using Extended Ephemeris injection as well as Extended Ephemeris on-board generation for fastest TTFF
- Easy integration in cellular/GNSS bundle solutions with Telit cellular modules
- GPS solution with embedded Flash: high performance, always up-to-date and lowest BOM cost and footprint

### Family Concept

Our positioning product portfolio is the result of over twenty years of experience in GNSS applications. Telit has developed a range of products compatible with the well-known GPS constellation as well as its Russian counterpart GLONASS. Moreover, our portfolio is fully aligned with the upcoming service launch of Europe's Galileo constellation. Valuable features such as Dead Reckoning, Precision Timing, as well as speed and reliability assured by multi-constellation coverage, provide additional benefits for your application.

Your application development effort can also benefit significantly from the seamless integration between Telit's 2G cellular and positioning modules. This bundling of cellular and positioning modules significantly reduces development complexity without adding costs. Multi-constellation positioning products applied together with our eCall / ERA-GLONASS compliant cellular modules bring you ready-to-use emergency automotive tracking solutions for the European and Russian markets.

Typical applications include fleet management systems, European GPS-assisted road tolling systems, cellular base stations, in-car navigation systems, automotive telematics systems, and GPS-based personal sports training monitors.

### Combine your GNSS module with

Cellular modules



Short Range modules



[www.telit.com](http://www.telit.com)

## JUPITER JF2

### Product Features

- Standards: NMEA and OSP
- 48 Channel GPS architecture
- Positional Accuracy (CEP50): Autonomous Positional Error < 2.5 m
- Accuracy
  - Speed: < 0.01 m/s
  - Heading: < 0.01 deg
- Time To First Fix (90% @ -130 dBm)
  - Hot Start: 1 s
  - Cold Start: < 35 s
- A-GPS: local ephemeris prediction
- A-GPS: server predicted ephemeris file injection

### Environmental

- Dimensions: 11 x 11 x 2.6 mm
- Weight: 1 g
- 32-pad QFN package, requiring only 2 layer PCB
- Temperature Range
  - Operating temperature: -40 to +85°C
  - Storage temperature: -40 to +85°C

### Interfaces

- UART, SPI, I<sup>2</sup>C interfaces
- PPS for precise timing
- EGNOS, WAAS, GAGAN and MSAS capability embedded with correction of positional errors due to ionospheric and orbital disturbances
- RTC for efficient power management

### Electrical & Sensitivity

- Current consumption
  - Hibernate Mode current: 14 uA
  - Low power mode (Tracking 1Hz): 10 mA
  - Full power Tracking: 37 mA
- Power supply
  - Range from 1.75 up to 1.9 V
- Sensitivity
  - Acquisition: -147 dBm
  - Navigation: -160 dBm
  - Tracking: -163 dBm



### Join the Telit Technical Forum

For a quicker and more rewarding integration experience join the Telit Technical Forum. There you can browse the first open forum covering all IoT topics, get direct support by region (EMEA, North America, Latin America, APAC), take part in this quickly growing IoT community and exchange experiences.