SAFETY DATA SHEET

POLYURETHANE FOAM CLEANER- Japan



SECTION 1- PRODUCT AND COMPANY IDENTIFICATION

1.1 Product Identifier

Product Name: Professional Foam Gun Cleaner

SDS ID Number 22011

1.2 Relevant identified uses of the substance or mixture and uses advised against

General Use Foam sealant remover, multi-purpose cleaner for professional use only

Uses advised against

1.3 Details of the supplier and of the safety data sheet

Manufacturer Aquascape Inc

901 Aqualand Way St. Charles, IL 60174

1.4 Emergency telephone numbers

In the U.S.A 866-877-6637 International Emergency 866-766-3426

SECTION 2- HAZARDS IDENTIFICATION

2.1 Classification of substance or mixture

Product definition: Mixture

Classification: Flammable Aerosol- Category 1

Gases Under Pressure- Compressed Gas

Eye Irritation- Category 2

Specific Target Organ Toxicity SE 3

2.2 Label elements **Hazard Symbols:**

Signal Word:

DANGER Hazard Statements: H222- Extremely flammable aerosol

H280- Contains gas under pressure; may explode if heated

H319- Causes serious eve irritation H336- May cause drowsiness or dizziness

Prevention: P102- Keep out of reach of children

P210- Keep away from heat/sparks/open flames/hot surfaces-No Smoking

P211- Do not spray on an open flame or other ignition source P251- Pressurized container: Do not pierce or burn, even after use

P260- Do not breathe mist/vapors/spray

P262- Do not get in eyes, on skin, or on clothing P270- Do not eat, drink or smoke while using this product

P271- Use only outdoors or in a well-ventilated area

P280- Wear protective gloves, protective clothing and eye protection

Response:

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing

P305+P351+P338- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. P314- Get medical advice if you feel unwell

P342+P311- If experiencing respiratory symptoms: Call a POISON CENTER or doctor

P370+P378- In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction

P381- Eliminate all ignition sources if safe to do so

Storage: P403+P405- Store in a well-ventilated place. Store locked up.

P410- Protect from sunlight

P412- Do not expose to temperatures exceeding 50°C/122°F.

Disposal: P501 Dispose of contents/container in accordance with applicable local/regional/national/international

regulations.

SECTION 3- COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	Ingredient	CAS No.	
>90	Acetone	67-64-1	
<10	Carbon Dioxide	124-38-9	

There are not additional ingredients present which, within the current knowledge of the supplier and in the concentration applicable, are classified as hazardous to the health or environment and hence require reporting in this section.

SECTION 4- FIRST AID MEASURES

4.1 Description of first aid measures

Eye: Immediately flush eyes with large amounts of water for at least 15 minutes, holding the eyes open with fingers and

occasionally lifting the upper and lower lids. Use lukewarm water if possible. If present and easy to do so, remove contact

lenses, if irritation persists, get medical attention.

Skin: In case of contact, immediately flush skin with plenty of soap and water. Remove contaminated clothing and shoes. Wash

clothing before reuse. Call a physician if irritation persists.

If product vapor or mist causes respiratory irritation or distress, move exposed person to fresh air immediately. If not

Inhalation: breathing, give artificial respiration. If breathing is difficult, give oxygen. Obtain medical attention.

Ingestion: Rinse mouth thoroughly with water. If swallowed, do NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3 Notes to the physician

Symptoms may not appear immediately. If case of an accident or if you feel unwell, seek medical advice immediately (show label or SDS if possible).

SECTION 5- FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable methods of extinction: Use dry chemical, carbon dioxide, alcohol resistant foam, Halon 1211, water spray or fog.

Unsuitable methods of extinction: Do not use water jets and high pressure water as these may spread the fire

5.2 Special hazards arising from the substance or mixture

Contents under pressure. Extremely flammable aerosol. Contains flammable liquid and vapor. Eliminate all ignition sources. Aerosol cans exposed to fire or high temperature can rupture and rocket. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas. During a fire irritating and highly toxic gases may be generated by thermal decomposition or combustion.

5.3 Advice to firefighters

Keep upwind of fire. Wear full fire-fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Containers may explode if heated.

SECTION 6- ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Stay upwind of spill. Keep out of low areas. Use personal protective equipment recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Avoid breathing vapor.

6.2 Environmental precautions

Do not allow to enter sewers, drains, or waterways

6.3 Methods and materials for containment and cleaning up

Method for containment: Contain spill. Absorb liquid with vermiculite or with an inert absorbent.

Methods for cleaning up: Scoop up material and place in a lidded disposal container. Dispose of as waste in accordance with all applicable guidelines and regulations. Materials used in clean-up may be considered hazardous waste. Vapors can accumulate in low areas. Provide ventilation.

6.4 Reference to other sections

For indications about waste treatment, see Section 13 See Section 7 for information on safe handling

SECTION 7- HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep away from sources of ignition- No smoking. Do not spray on an open flame or other ignition source. Pressurized container: do not pierce or burn, even after use. Container may explode if heated. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Do not swallow. Use only in a well-ventilated area or outdoors. Avoid welding or other "hot work" in the vicinity using Handi-Cleaner. When using do not eat, drink or smoke. (See section 8)

General hygiene advice: Launder contaminated clothing before reuse. Wash hands before eating, drinking or smoking.

7.2 Conditions for safe storage including any incompatibilities

Store in a dry place. Store locked-up. Do not expose aerosol cans to open flame or temperatures above 122°F (50°C). Protect containers from physical abuse. Keep containers upright. **KEEP AWAY FROM CHILDREN.**

SECTION 8- EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1 Control Parameters

CAS No.	Ingredient	OSHA-PEL TWA	ACGIH-TLV	NIOSH
67-64-1	Acetone	1000 ppm 2400 mg/m ³	500 ppm TWA 750 ppm STEL	250 ppm; 590 mg/m³ TWA 2500 ppm IDLH (LEL)
124-38-9	Carbon Dioxide	5000 ppm 9000 mg/m ³	5000 ppm; 9000 mg/m ³ TWA 30000 ppm; 54000 mg/m ³ STEL	1000 ppm; 1900 mg/m³ TWA 30000 ppm; 54000 mg/m³ STEL 40000 ppm IDLH

8.2 Exposure Controls:

Engineering measures: Use ventilation adequate to keep exposures below recommended exposure limits.

Eye/face Protection: Wear protective safety glasses with side shields or goggles.

Hand Protection: Use chemically resistant gloves (i.e. Nitrile gloves). Nitrile/butadiene rubber, butyl rubber, polyethylene, PVC (vinyl), or neoprene gloves are also effective. Glove selection should take into account potential body reactions to certain materials and manufacturer's instructions for use. Break through time of selected gloves must be greater than the intended use period.

Other Protective Equipment: Use clothing that protects against dermal exposure. Appropriate protective clothing varies depending on the potential for exposure. To ensure proper skin protection, wear PPE in such a manner that no skin is exposed.

Respiratory Protection: If atmospheric levels are expected to exceed the exposure levels, use a NIOSH approved air purifying respirator equipped with an organic vapor cartridge and particulate filter. If atmospheric levels exceed 10 times the TLV or PEL level for which an airpurifying respirator is effective, use a powered air purifying respirator (PAPR). The type of respiratory protection selected must comply with the requirements set forth in OSHA's Respiratory Protection Standard (29 CFR 1910.134).

Hygiene Measures: An eye wash station or portable eye wash station should be in the area. Wash hands thoroughly after use, before eating, drinking or using the lavatory. Employees/Users should be educated and trained in the safe use and handling of this product.

SECTION 9- Physical and chemical properties

9.1 Information on basic physical General Physical Form	Aerosol- Clear colorless liquid
Color	Clear
Odor	Solvent Odor
Odor Threshold:	13-20 ppm
pH:	7
Melting Point/Freezing Point	No data available
Initial Boiling Point and Boiling Range	133°F (56.°C) (Acetone Supplier)
Flash Point:	0°F (-18.°C), (Acetone Supplier
Evaporation Rate:	5.6
Flammability:	Highly Flammable
Lower Flammability/Explosive Limit:	2.5%
Upper Flammability/Explosive Limit:	12.8%
Vapor Pressure	231 mm Hg @ 25°C)
Vapor Density:	2.0 (Air = 1)
Relative Density/Specific Gravity:	~ .81 estimated (Water = 1)
Solubility:	Soluble

Partition coefficient: n-octanol/water:	log Pow = -0.24
Auto-ignition Temperature:	1004°F (540°C)(Acetone Supplier)
Decomposition Temperature;	No data available
Viscosity:	.33 cps @20°C
Explosive Properties:	May be sensitive to mechanical impact or static discharge. Vapor released during and immediately after dispensing may accumulate and ignite explosively if proper ventilation is not employed. Extinguish or remove all sources of ignition during dispensing, until product becomes tack free or skins over.
VOC Content (calculated minus exempt compounds and water)	0 g/l (acetone and carbon dioxide are VOC exempt compounds)

SECTION 10- STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical Stability

Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not pierce or burn, even after use.

10.3 Possibility of Hazardous Reactions

Contents are under pressure and exposure to high temperature can cause containers to rupture or explode. Avoid excessive heat and sources of ignition. Reacts with strong oxidizing agents.

10.4 Conditions To Avoid

Heat. Incompatible materials. Sources of ignition.

10.5 Incompatible Materials

Strong oxidizing agents, strong acids, halogenated compounds, reducing agents, strong bases, rubber, various plastics.

10.6 Hazardous Decomposition Products

May include, and are not limited to: oxides of carbon, irritating and toxic fumes.

SECTION 11- TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure based on test data and/or information on the components, this material may produce the following health effects:

Eye: Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision

Skin: May cause skin irritation. Repeated or prolonged exposure may cause drying and cracking of skin. May be absorbed by the skin.

Inhalation: May be harmful if inhaled. High concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, or drowsiness.

Ingestion: May be harmful if swallowed. May cause gastrointestinal irritation: stomach distress, nausea, or vomiting.

Acute Oral Toxicity

LD50, rat: 5800 mg/kg (acetone)

Acute inhalation toxicity

LC50, rat: 55700 ppm, 3h (acetone)

Acute dermal toxicity

LD50, rabbit: 7426mg/kg, 24h (acetone)

Skin irritation

May cause skin irritation

Eye irritation

Causes serious eye irritation

Sensitization

No data available

Genotoxicity

In vivo: Mutagenicity (mammal cell test)- Micronucleus; Result-negative

In vitro: Ames test; Result- negative

In vitro: Mutagenicity (mammal cell test)- Chromosome aberration; Result-negative

Mutagenicity

Test data using laboratory animals was predominately negative

Specific organ toxicity- single exposure

May cause drowsiness or dizziness

Specific organ toxicity- repeated exposure

No data available

Aspiration hazard- no data available

11.2 Further Information:

Acetone: ACIGH A4 Carcinogen-Not classifiable as a human carcinogen. Not listed as a carcinogen by IARC, OSHA or NTP. No data is available regarding the mutagenicity or teratogenicity of this product, nor is there any available data that indicates that it causes adverse developmental or fertility effects.

ISSUE DATE: March 2005

SECTION 12- ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Aquatic Ecotoxicity (Acetone):

LC50 Oncorhynchus mykiss (Rainbow trout) 96h: 5,540 mg/l

LC50 Pimephales promelas (Fathead minnow) 96h: 7,280-8180 mg/l

LC50 Lepomis macrochirus 9Bluegill sunfish) 96h: 8,300 mg/l

Acute toxicity to aquatic invertebrates:

EC50 Daphnia magna (Water flea) 48h: 6,100 mg/l

Acute and prolonged toxicity to aquatic plants:

EC50 Selenastrum capricorntum (Green algae) 96h: >100 mg/l

Acute toxicity to aquatic microbes:

EC50 Activated sludge- 30 min: 59-67.4 mg/l

12.2 Persistence and degradability

Product is not readily biodegradable.

12.3 Bioaccumulative potential

Does not bioaccumulate

12.4 Mobility in soil

Material volatizes, leeches and biodegrades when released to soil

12.5 Other Adverse Effects

Additional ecological information:

Do not allow material to run into surface waters, waste water or soil.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13- DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Methods of disposal

Before disposing of containers, collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material must be disposed of in accordance with all local, regional, national, international regulations.

RCRA Hazardous Waste U List: Acetone (CAS 67-64-1) U002

Other disposal recommendations:

Do not puncture or incinerate containers. Use appropriate Personal Protective Equipment.

SECTION 14- TRANSPORTATION

Ground	Limited Quantity
Air	UN1950 Aerosols, Flammable 2.1 (Flammable Gas Label) LIMITED QUANTITY Packing Instructions (Cargo & Passenger) 203
Water	UN1950 Aerosols, Flammable 2.1 (Flammable Gas Label) LIMITED QUANTITY

SECTION 15- REGULATORY

15.1 Safety, health, and environmental regulations/ legislations specific for the substance or mixture U.S. Federal Regulations

OSHA Hazard Communication Standard: This material is classified as a hazardous in accordance with OSHA 29 CFR 1910-1200

PAGE 6 OF 6

TSCA Status: All components of this product are listed on the Toxic Substance Control Act (TSCA) Inventory. This product is not subject to TSCA 12(b) Export Notification.

Superfund Amendments and Reauthorization Act (SARA)

SARA Section 311/312 Hazard Categories: Acute Health Hazard, Fire Hazard, Sudden Release of Pressure Hazard

SARA 313 Information: None of the chemicals in this product exceed the threshold (de minimis) reporting levels established by Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986.

SARA 302/304 Extremely Hazardous Substance: No components of the product exceed the threshold (de minimis) reporting levels established by these sections of the Title III of SARA.

SARA 302/304 Emergency Planning & Notification: No components of the product exceed the threshold (de minimis) report levels established by these sections of the Title III of SARA.

Comprehensive Response Compensation and Liability Act (CERCLA): This product contains the following CERCLA reportable substances: Acetone (CAS #67-64-1): RQ- 2,268 kg (5,000 lbs).

Clean Air Act (CAA) – This product does not contain any chemicals that are listed as a Hazardous Air Pollutant (HAP) designated in CAA Section 112 (b). This product does not contain any Class 1 or Class 2 Ozone depletors.

Clean Water Act (CWA) - Acetone (CAS #101-68-8) is listed as a Hazardous Substance under the CWA. None of the chemicals in these products are listed as Priority Pollutants under the CWA. None of the chemicals listed in these products are listed as Toxic Pollutants under the CWA.

U.S. State Inventories:

Acetone (CAS #67-64-1) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air Quality/air Pollutants lists: CA, DE, FL, ID, ME, MA, MN, NJ, PA, RI

Carbon Dioxide (CAS #124-38-9) is listed on the following State Hazardous Substance Inventories, Right-to-Know lists and/or Air

Quality/Air Pollutants lists: NJ, MA, PA, RI Global Chemical Inventory Lists:

United States: Toxic Substance Control Act (TSCA)- Yes

Japan: ENCS- Yes

15.2 Chemical safety assessment: For this product, a chemical safety assessment was not carried out

SECTION 16- OTHER









NFPA: Health Hazard 1; Flammability 3; Reactivity 0
HMIS: Health Hazard 1; Flammability 3; Physical Hazard 0

Hazard Rating: 0=minimal, 1= slight, 2=moderate, 3=severe, 4= extreme

The information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof. The manufacturer makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will the manufacturer be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. No representations or warranties, either expressed or implied, of merchantability or fitness for a particular use are made hereunder with respect to this information or the product to which information refers.

Information contained herein is deemed to be reliable, conservative and accurate. ICP Building Solutions Group reserves the right to change the design, specifications or any other features at any time and without notice, while otherwise maintaining regulatory compliance.

Revision- January 30, 2020 Version 1.5 (Replaces June 18,2013-4)