

4E SERIES

ROPS & CAB

62 - 95^{HP}



Known for exceptional cab comfort, with car-like tech and features, the 4E Cabin Series offers three models ranging in output from 62 hp to 95 hp. Highly manoeuvrable and offered with STOLL loader options, standard features include engine speed programming, synchro shuttle with splitter, 4 wheel wet disc brakes and high capacity hydraulics.

Or choose the efficient 85 hp 4E ROPS, ideal for raking, slashing, feeding out and day-to-day farming tasks. With an ISO mounted platform, intuitive controls, clever ergonomics and remarkable visibility, the 4E ROPS carries many of the same features of a cabin tractor. All 4E series tractors are equipped with a forward / reverse shuttle synchronised transmission; a must when doing loader work.



4E CABIN



4E ROPS



4065E

CAB

62HP

4080.4E

CAB

80HP

4090.4E

ROPS

85HP

4100.4E

CAB


95HP

DEUTZ-FAHR



1800 789 633

| TECHNICAL DATA & FEATURES | 4065E CAB | 4080.4E CAB | 4090.4E ROPS | 4100.4E CAB |
|---------------------------|-----------|-------------|--------------|-------------|
|---------------------------|-----------|-------------|--------------|-------------|



| POWER + PERFORMANCE | | | | |
|---------------------|--|--|--|--|
|---------------------|--|--|--|--|

| | | | | |
|------------------------------|----------------------------|-------------------|---------|-------|
| Engine Type | Deutz-Fahr SDF 1000 Series | | | |
| Emissions | Tier III A | | | |
| Cylinders / Capacity | 3/3000 | 4/4000 | | |
| Aspiration | Turbo | Turbo Intercooler | | |
| Max Power - ECE R120 (kW/HP) | 45.6/62 | 58.8/80 | 62.5/85 | 70/95 |
| Max Torque (Nm) | 240 | 325 | 348 | 373 |
| Rated Engine Speed (rpm) | 2200 | | | 2000 |
| Fuel Capacity (l) | 70 | | | |

| DRIVE + HANDLING | | | | |
|------------------|--|--|--|--|
|------------------|--|--|--|--|

| | | | | |
|-------------------------|------------------------------------|----------------------|--|--|
| Gearbox Type and Gears | Synchronised Shuttle | | | |
| Number of Gears | 30+15 | | | |
| Forward/Reverse Shuttle | ■ | | | |
| Clutch Type | Double Dry HD 11" | Double Dry HD 12" | | |
| Min Speed (km/h) | 0.23 | | | |
| Max Speed (km/h) | 40 | | | |
| 4WD | ■ | | | |
| Diff Lock | Mechanically Operated Front + Rear | | | |
| Brakes (NO / Type) | 4/ Independent Wet Disc | | | |
| Wheel Size - Rear | Adjustable 340/85R28 | Adjustable 420/85R30 | | |
| Wheel Size - Front | Adjustable 9.5R20 | Adjustable 320/70R24 | | |
| PTO Type | Mechanical Independent | | | |
| Speeds - Rear | 540 / 750 | | | |
| PTO engine speed (rpm) | 1967 / 1560 | | | |

| LIFT + FLOW | | | | |
|-------------|--|--|--|--|
|-------------|--|--|--|--|

| | | | | |
|-------------------------------|----------------------------|-----------------------------|--|--|
| Type | Open Centre | | | |
| Flow Rate (l/min) | Steering 17 / Hydraulic 42 | | | |
| Remote Valves (sets) | 2 | 3 | | |
| Remote Valve Type | Spring | 2 Detent + Spring / 1 Float | | |
| 3 Point Hitch Type | Mechanical with Draft | | | |
| Category | 2 | | | |
| Hitch End Type | Ball | | | |
| Max Lift Capacity - Rear (kg) | 2500 | 3500 | | |

| COMFORT + CONVENIENCE | | | | |
|-----------------------|--|--|--|--|
|-----------------------|--|--|--|--|

| | | | | |
|---------------------------------------|--------------------|---|-------------------|--------------------|
| Air-Conditioned Cabin | ■ | - | - | ■ |
| Digital Climate Control | ■ | - | - | ■ |
| 2 Post ROPS | - | - | ■ | - |
| Sun Canopy | - | - | ■ | - |
| Driver Seat w/ Mechanical Suspension | ■ | | | |
| Adjustable Steering Wheel | ■ | | | |
| Display | Analogue | | | |
| Side Control Levers | ■ | | | |
| Engine Speed Programming | - | ■ | | |
| EASYLIFT Three Point Linkage | ■ | | | |
| Flat Platform Mounted on Silent-Block | ■ | | | |
| Upswept Side Mounted Exhaust | ■ | | | |
| Worklights (No + Type) | 2 Bonnet / 4 Cabin | | 2 Bonnet / 1 Rear | 2 Bonnet / 4 Cabin |

| WEIGHTS + DIMENSIONS | | | | |
|----------------------|--|--|--|--|
|----------------------|--|--|--|--|

| | | | | |
|------------------------|------|------|------|------|
| Wheelbase (mm) | 1976 | 2106 | | |
| Length (mm) | 3730 | 3990 | | |
| Mid Overall Width (mm) | 1800 | 1830 | | |
| Height (mm) | 2607 | 2666 | 2563 | 2666 |
| Weight (kg) | 2950 | 3250 | 3100 | 3250 |

■ Standard



CAB MODEL




ROPS MODEL



FOUR WHEEL WET DISC BRAKES



FORWARD/REVERSE SHUTTLE



DIGITAL CLIMATE CONTROL