

AGROFARM G SERIES




A step up in power and comfort, the two Agrofarm G Series models are available as cabin or ROPS versions and produce 96 hp and 110 hp respectively. Designed for our variable Australian conditions, these superbly designed tractors are renowned their heavy-duty frame and manoeuvrability, a distinct advantage with a loader fitted.

Built for multi-purpose farming, they feature a high capacity hydraulic pump, 4 wheel independent wet disc brakes and choice of two transmission types, wet clutch Powershuttle or dry clutch synchro shuttle. Visibility is outstanding, likewise the torque developed by the Deutz-Fahr SDF 1000 Series 4 cylinder turbo intercooled engine. The Agrofarm G Series represents real value for money.



CABIN









| TECHNICAL DATA & FEATURES | AGROFARM 100DT CAB | AGROFARM 115GS CAB | AGROFARM 115GS ROPS |
|---|---|--------------------|--|
| POWER + PERFORMANCE | | | |
| Engine Type | Deutz-Fahr SDF 1000 Series | | |
| Emissions | Tier I | | |
| Cylinders / Capacity | 4/4000 | | |
| | Turbo Turbo Intercooler | | |
| Aspiration Max Power - ECE R120 (kW/HP) | 70.6/96 81/110 | | |
| · | 342 396 | | |
| Max Torque (Nm) | | | |
| Rated Engine Speed (rpm) | 2300 2350 150 | | |
| Fuel Capacity (I) DRIVE + HANDLING | | 150 | |
| Gearbox Type and Gears | Synchronised Shuttle Wet Clutch Power Shuttle | | |
| Number of Gears | 20+20 | 30+30 | 40+40 |
| | | | 40+40 |
| Powershift Speeds | - 2 | | |
| Forward/Reverse Shuttle | C. K. A. F. antina D. a. H. and D. a. 12// | | |
| Clutch Type | Self-Adjusting Dry Heavy Duty 13" | Wet Clut | |
| Min Speed (km/h) | 0.20 | 2.01 | 0.22 |
| Max Speed (km/h) | 40 | | |
| 4WD | • | | |
| Diff Lock | Electro-Hyd Operated Front + Rear | | |
| Brakes (N0 / Type) | 4/ Independent Wet Disc | | |
| Wheel Size - Rear | Adjustable 480/70R34 | | |
| Wheel Size - Front | Adjustable 420/70R24 | | |
| РТО Туре | Electro-Hyd Independent Wet Clutch | | |
| Speeds - Rear | 540/540E/1000/1000E 540/1000 | | |
| PTO engine speed (rpm) | 2077/1654/2250/1783 2077/2250 | | 2077/2250 |
| LIFT + FLOW | | | |
| Туре | Open Centre | | |
| Flow Rate (Type + I/min) | Steering 44 / Hydraulic 56 | | |
| Remote Valves (sets) | 2 3 | | |
| 3 Point Hitch Type | Mechanical with Draft | | |
| Category | 2 | | |
| Hitch End Type | Hook | | Ball |
| Max Lift Capacity - Rear (kg) | 4200 | 4800 | 4200 |
| COMFORT + CONVENIENCE | | | |
| Air-Conditioned Cabin | ■ | | |
| Radio/MP3 Player | • | | - |
| 2 Post ROPS | - | - | |
| Sun Canopy | | - | |
| Cloth Driver Seat w/ Pneumatic Suspension | | | - |
| PVC Driver Seat w/ Mechanical Suspension | - | - | _ |
| Adjustable Steering Wheel | | • | |
| Display | Analogue / Digital | | |
| Side Control Levers | • | | |
| Engine Speed Programming | | | |
| Flat Platform Mounted on Silent-Block | • | | |
| Upswept Side Mounted Exhaust | • | | |
| Worklights (No + Type) | | | 2 Bonnet / 2 Rear |
| WEIGHTS + DIMENSIONS | | | |
| Wheelbase (mm) | 2310 | 2310 2340 | |
| Length (mm) | 3850 | 3990 | |
| Min Overall Width (mm) | 2082 | | |
| Height (mm) | 2790 | | 2710 |
| Weight (kg) | 4100 | 4250 | 3650 |
| Weight (kg) | 4100 | 4230 | ■ Standard |
| | | | a purposes only. For exact specifications of |