

PD6

Pure Resonance Audio PD6 6.5" 2-Way
Open-Ceiling Pendant Mount Loudspeaker - Black

DESCRIPTION:

Designed to meet the needs of indoor and outdoor open-ceiling commercial applications, the Pure Resonance Audio PD6 6.5" full-range pendant speaker is weather-resistant, high powered and easy to install. This 70-volt pendant mount loudspeaker is perfect for restaurants, retail stores, offices, warehouses, or any other open-architecture high ceiling environment where paging, announcements or foreground and background music is required.

FEATURES:

- Durable weather-resistant construction for indoor and outdoor use
- 70 Volt/100 Volt transformer with 8 Ohm bypass
- 6.5" Polypropylene woofer and 1" silk tweeter
- 87 dB sensitivity provides quality sound
- Easy and secure installation with included pendant mounting hardware
- Euroblock screw terminal connector
- Available in black (PD6) and white (PD6W)



PRODUCT SPECIFICATIONS:

| | |
|--|------------------------------------|
| Power Rating | 30 Watts RMS; 70 Watts Peak |
| Frequency Response (± 10 dB) | 65 Hz – 20 kHz |
| Sensitivity | 87 dB 1m/1w |
| Max SPL | 101 dB |
| Dispersion | Conical 150° |
| Impedance | 8 Ohms |
| Transformer Taps (70V) | 4W / 8W / 16W / 32W / 8 Ohm Bypass |
| Woofer | 6.5" Polypropylene |
| Tweeter | 1" Silk |
| Grill | Powder-coated aluminum |
| Connection | 4-pin Euroblock screw terminal |
| Dimensions (H x Dia) | 10.3" (285 mm) x 8.1" (207 mm) |
| Weight | 6.35 lbs (2.88 kg) |
| Shipping Dimensions (H x W x D) | 11.25" x 13.5" x 10.56" |
| Shipping Weight | 9 lbs (4.08 kg) |