# Technical Data Sheet



# **160ELITE-ULTRA**

**Environment Learning Extraction Fan** 


#### **Dimensions**


Cut-out size for inlet fascia

170mm


Cut out size for outlet fascia


158mm

















## **Specifications**

Weight 3.5kg
Colour of front fascia White
Housing material FR Glo

FR Glass filled nylon

### **Approval**

AS/NZS 603350.2.80:2004 Amdt .1.2009 AS/NZS 60335.1.2011 incl Amdt.1.2012

#### **Features**

- Easy to install even through 13mm Gib
- Built in controller with on demand extraction
- 6 metres of 150mm diameter ducting
- 12Volt LED driver included.
- Lamp: Warm white (3000K) or Cool white (6500K)
- Safe for use over shower stall
- Allows moisture to be removed to the outside of your home
- All parts are included
  - 5 year extended warranty

# Technical Data Sheet

#### **Product Use**

The 160ELITE-ULTRA is used for the extraction of mist and lighting
Safe for use in wet areas

Typical applications:

- Bathrooms
- Toilets
- Laundries

#### **Environmental Conditions**

Operation to IEC 721-3-3
Climatic conditions class 3K5
Temperature 0...+50°C
Humidity <95% r.h.

#### **Standards**

Test standards AS/NZS

603350.2.80:1T

Amdts 1-3 "Electric

Fans".

EMC Compliance This is a Level One

product with a brushless DC motor that has a very low risk of causing EMC

interference

#### General

Installed Fan Performance 590m³/ hr 163.4L/sec

Installed decibel rating 31DB

### **Ordering**

When ordering please give name and type, Reference 160ELITE-ULTRA Barcode

#### **Technical Data**

Power supply 230 VAC

Power consumption max. 0.019~0.45A

Supply Line Fusing max. 10A
Connection terminals screw clamp

terminals

For solid wires 2 x 1.5mm<sup>2</sup>
Max product wattage 73Watts
Free air fan performance 63~650m³/hr