

**MATERIAL SAFETY DATA SHEET**  
**FOR COATINGS, RESINS AND RELATED MATERIALS**

**Date Issued 04/07/2009**

**SECTION I**

MANUFACTURERS NAME

**GARDNER GIBSON CORPORATION**

STREET ADDRESS

**4161 E 7<sup>TH</sup> AVENUE**

CITY, STATE, AND ZIP CODE

**TAMPA, FL 33605**

EMERGENCY TELEPHONE NUMBER

**1-800-424-9300 CHEMTREC**

PRODUCT CLASS

**ALUMINUM NON-FIBERED ALUMINUM ROOF  
COATING**

MANUFACTURER'S CODE

IDENTIFICATION

**5051**

TRADE NAME

**PRO'S CHOICE**

**SECTION II- HAZARDOUS INGREDIENTS**

INGREDIENT	PERCENT	TLV PPM	TLV Mg/M3
MINERAL SPIRITS <b>CAS #- 8052-41-3</b>	<50%	100	NA
PETROLEUM ASPHALT <b>CAS #- 8052-42-4</b>	<40%	NA	0.5 Fume
ALUMINUM PASTE <b>CAS #- MIXTURE</b>	<20%	100	NA
INORGANIC FILLER <b>CAS #- 1317-65-3</b>	<10%	NA	10*

ADDITIONAL INFORMATION-\*AS RESPIRABLE FRACTION OF DUST.

**Hazardous Materials Identification System (HMIS)**

Health  
1

Flammability  
2

Reactivity  
0

Personal Protection  
B

**SECTION III – PHYSICAL DATA**

BOILING RANGE: 300 °F - 390°F

VAPOR DENSITY  HEAVIER

EVAPORATION RATE  SLOWER THAN ETHER

PERCENT VOTILE BY  
VOLUME 50 %

WEIGHT PER GALLON  
BY VOLUME 8.0 LBS

**SECTION IV – FIRE AND EXPLOSION HAZARD DATA**

DOT CATEGORY – NOT REGULATED

FLASH POINT- 105°F Minimum

EXTINGUISHING MEDIA- CO2, FOAM, & DRY CHEMICAL

UNUSUAL FIRE AND EXPLOSION HAZARDS- CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. PRODUCTS OF COMBUSTION MAY BE TOXIC

SPECIAL FIRE FIGHTING PROCEDURES- WEAR SELF CONTAINED BREATHING APPARATUS. WATER MAY BE USED TO COOL CLOSED CONTAINERS. HIGH PRESSURE STREAM WILL SPREAD FIRE.

---

## SECTION V – REACTIVITY DATA

---

STABILITY:  STABLE

CONDITIONS TO AVOID: HEAT, FLAMES, STRONG  
OXIDIZERS

INCOMPATIBILITY (MATERIALS TO AVOID): CARBON OXIDES

HAZARDOUS DECOMPOSITION PRODUCTS: NONE

HAZARDOUS POLYMERIZATION:  WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

---

## SECTION VI-HEALTH HAZARD DATA

---

EFFECTS OF OVEREXPOSURE-ACUTE: SKIN: PROLONGED /REPEATED CONTACT MAY CAUSE IRRITATION, DEFATTING AND DERMATITIS. -EYES: MAY CAUSE SEVERE IRRITATION, REDNESS TEARING AND BLURRED VISION. -INHALATION: MAY CAUSE DIZZINESS, WEAKNESS, HEADACHE, UNCONSCIOUSNESS AND EVEN ASPHYXIATION. -INGESTION MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. CARCINOGENICITY: MATERIAL CONTAINS PETROLEUM ASPHALT. IARC HAS DETERMINED THAT THERE IS INADEQUATE EVIDENCE THAT ASPHALT ALONE IS CARCINOGENIC TO HUMANS. IN SOLUTIONS, SOLVENT EXTRACTS CAN PRODUCE SKIN CANCER IN ANIMALS, FOLLOWING PROLONGED AND REPEATED CONTACT. IARC HAS CONCLUDED THAT THERE IS SUFFICIENT EVIDENCE OF THE CARCINOGENICITY OF ASPHALT EXTRACTS. THEREFORE, CUTBACKS LIKE THIS PRODUCT MAY ALSO BE IMPLICATED AS POTENTIALLY CARCINOGENIC. PLEASE FOLLOW MSDS PRECAUTIONARY MEASURES. SYNERGISTIC MATERIALS: N/A REPRODUCTIVE EFFECTS: ND TERATOGENIC: NO MUTAGENIC: NO.

---

EMERGENCY FIRST AID PROCEDURE-SKIN: REMOVE CONTAMINATED CLOTHING. WASH EXPOSED AREA. WITH SOAP AND WATER. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXIGEN. IF BREATHING STOPS, GIVE ARTIFICIAL RESPIRATION AND SEEK MEDICAL ATTENTION IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING. KEEP PERSON WARM AND QUIET. ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL.

---

## SECTION VII – SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ELIMINATE SOURCES OF IGNITION KEEP PRODUCT OUT OF SEWERS BY DIKING OR IMPOUNDING. SOAK UP SPILL WITH SAND OR OTHER ABSORBENT. PLACE IN CONTAINERS. WASH AREA.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

---

## SECTION VIII – SPECIAL PROTECTION INFORMATION

---

RESPIRATORY PROTECTION: USE NIOSH/MSHA APPROVED RESPIRATOR WHEN TLV IS EXCEEDED.

VENTILATION: USE WITH ADEQUATE VENTILATION.

PROTECTIVE GLOVES: NITRILE RUBBER SHOULD BE USED.

EYE PROTECTION: SAFETY GOGGLES SHOULD BE USED.

OTHER PROTECTIVE EQUIPMENT: FACE SHIELD

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE IN COOL PLACE

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINERS TIGHTLY CLOSED.

---

---

## SECTION IX – REGULATORY INFORMATION

---

**DOT CATEGORY:** NOT REGULATED

**TSCA STATUS:** ALL CHEMICAL SUBSTANCES IN THIS PRODUCT ARE INCLUDED ON OR EXEMPTED FROM LISTING ON THE TSCA INVENTORY OF CHEMICAL SUBSTANCES.

**CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ).**  
**WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Read and follow label directions and information given on Material Safety Data Sheets and use care when handling or using all petroleum products.