



STEP #6:
 APOC REFLECTIVE ROOF
 COATING.
 ALLOW FLASHING
 CEMENT TO PROPERLY
 CURE PRIOR TO COATING
 ALL EXPOSED BASE
 FLASHING.

STEP #5:
 APOC #525
 ARMORFLEX

STEP #4:
 APOC FLASHING
 CEMENT

STEP #3:
 TERM-BAR

STEP #2:
 APOC #567 PRO-TACK SELF ADHERED
 MEMBRANE (MIN 6" FROM TOE OF CANT).
 EMBEDDED IN A LAYER OF APOC
 FLASHING CEMENT.

STEP #1:
 APOC #103 PRIMER

EXISTING ROOF
 MEMBRANES
 & FLASHING

APOC NOTES:

1. FOLLOW APOC - ARMORFLEX ROOF RESTORATION SPECIFICATION GUIDELINES.
2. FOLLOW APOC MATERIAL PREPARATION AND APPLICATION RATES, INCLUDING ARMORFLEX #525 SURFACING COMPOUND AND APPROVED TOP SURFACING OPTIONS.

<p>BASE FLASHING FOR WALL-SUPPORTED DECK</p>	<p>ARM-3</p> <p>NOT DRAWN TO SCALE</p>
----------------------------------------------	----------------------------------------