



# PRODUCT CATALOG

► The Roof Restoration Experts™



*Con información en español*

# ▼ ROOF & FLASHING CEMENTS

CEMENTOS PARA FLASHINGS Y TECHOS

100



## PRO-GEL® PLASTIC Roof Cement



**COMPLIANCE:** • Miami-Dade Approved  
• Exceeds ASTM D 4586  
• ASTM D 6511 • Asbestos Free

Thick Trowel Grade  
Heavy Bodied for Warmer Climates

*Espeso, aplicación con paleta  
Consistencia robusta para climas calurosos*

101



## WORK-HORSE® PLASTIC Roof Cement



**COMPLIANCE:** • Miami-Dade Approved  
• Exceeds ASTM D 4586  
• ASTM D 6511 • Asbestos Free

Trowel Grade Cement  
Great for Flat or Vertical Surfaces

*Cemento de calidad aplicado con paleta  
Excelente para las superficies planas o verticales*

\*\*Available in: SG, IG, WG

109



## RAIN PROOF® WET/DRY Roof Cement



**COMPLIANCE:** • Miami-Dade Approved  
• ASTM D 6511 • Exceeds ASTM D 4586  
• ASTM D 3409 • Asbestos Free

Light Trowel Grade  
Stops Leaks on Wet Surfaces

*Calidad de aplicacion liviana aplicado con paleta  
Detiene las goteras en las superficies mojadas*

\*\*Available in: SG, IG, WG

121



## ARIZONA® PLASTIC Roof Cement



**COMPLIANCE:** • ASTM D 6511  
• Exceeds ASTM D 4586  
• ASTM D 3409 • Asbestos Free

Heavy Duty Mastic  
Ideal for Hot Desert Climates

*Masilla de alta resistencia  
Ideal para los climas calurosos del desierto*

\*\*Available in: SG, WG

\* Regional Availability

122



## PREMIUM Flashing Cement



**COMPLIANCE:** • Miami-Dade Approved  
• ASTM D 6511 • ASTM D 3409  
• ASTM D 4586 • Asbestos Free

Premium Grade Flashing Cement  
Easy Spread for Flat, Vertical, and Wet Surfaces

*Cemento de primera calidad para flashing  
Fácil de aplicar en superficies planas, verticales y  
mojadas*

\*\*Available in: SG, IG, WG

\*\* Designates Products Available in:

SG - Summer Grade, IG - Intermediate Grade, and WG - Winter Grade



# ▼ RUBBERIZED FLASHING CEMENTS

CEMENTOS ENGOMADOS PARA FLASHING



PRS



## PRS - PROFESSIONAL ROOF SEALER™ Elastic Flashing Cement



5 U.S. GAL

COMPLIANCE: • Miami-Dade Approved  
• ASTM D 6511 • ASTM D 3409  
• ASTM D 4586 • Asbestos Free

Premium All Weather Elastic Cement  
Great for Flat or Vertical Surfaces

*Cemento elástico de primera calidad para todos los climas  
Excelente para las superficies planas o verticales*

\*\*Available in: SG, IG, WG

\* Regional Availability

133



## PRO-LASTIC® SBS MODIFIED Flashing Cement



5 3 1 U.S. GAL

COMPLIANCE: • Miami-Dade Approved  
• ASTM D 6511 • ASTM D 4586  
• ASTM D 3409 • Asbestos Free

Premium SBS Modified Cement  
Superior Adhesion, Lap Strength, and Sag Resistance

*Cemento modificado SBS de primera calidad  
Adherencia superior, fuerza en el solapado y resistencia al  
doblégar*

\*\*Available in: SG, IG, WG

365



## ETERNA-FLASH® ALL WEATHER/SEASON SBS Flashing Cement



3.5 1 U.S. GAL | TUBE

COMPLIANCE: • Miami-Dade Approved  
• ASTM D 3409 • ASTM D 6511  
• ASTM D 4586 • Asbestos Free

Ultimate All Weather/All Season Use  
Unmatched Performance and Durability

*Lo último de uso en todos los climas/todas las temporadas  
Rendimiento y durabilidad sin igual*

\*\*Available in: SG, WG

\*\* Designates Products Available in:

SG - Summer Grade, IG - Intermediate Grade, and WG - Winter Grade



## ▶ APOC® 365 ETERNA-FLASH™ All Weather/All Season SBS Flashing Cement

APOC® 365 is an extremely versatile, highly modified rubberized mastic that is specially formulated for the professional roofer. APOC® 365 provides superior adhesion to wet surfaces while at the same has sag resistance characteristics in warmer climates. APOC® 365 ETERNA-FLASH™ provides an 'E-Z Spread' durable repair compound that is ideal for repairs in any weather condition.

Use 365, it's the only mastic you'll ever need.

# ▼ ROOF PRIMERS, ADHESIVES & COATINGS

IMPRIMADORES, ADHESIVOS Y RECUBRIMIENTOS DE TECHO

103



## FAST DRY Asphalt Primer



COMPLIANCE: • Miami-Dade Approved  
• Compliant with SCAQMD • ASTM D 41  
• Asbestos Free



High Penetrating Formula  
Provides Superior Adhesion of Roofing Materials

*Fórmula de alta penetración  
Proporciona adherencia superior en materiales de techado*

107



## FIBREX® COLD PROCESS Cement and Adhesive



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved  
• ASTM D 3019 • Asbestos Free

Bonds Rolled Roofing & Granules  
Interply Adhesive in Cold Systems

*Pega el techado enrollado y los gránulos  
Adhesivo para interlaminaciones en los sistemas fríos*

108



## ROOF BOND DOUBLE COVERAGE Cement and Adhesive



COMPLIANCE: • Miami-Dade Approved  
• ASTM D 3019  
• Asbestos Free

Bonds Rolled Roofing & Granules  
Light Brush Grade

*Adhesivo para interlaminaciones en los sistemas fríos  
Pega el techado enrollado y los gránulos*

\*Regional Availability

136



## DURABOND® MBA ELASTOMERIC Rubberized Adhesive



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved  
• Exceeds ASTM D 3019 • Asbestos Free

Highly Modified SBS Interply Adhesive  
Tenacious Tack and Lap Strength

*Adhesivo SBS altamente modificado para interlaminaciones  
Con fuerza superior para el solapado*

200



## NON-FIBERED Roof Coating



COMPLIANCE: • Miami-Dade Approved  
• ASTM D 3019  
• Asbestos Free

Prevents Rust & Oxidation  
Use on Metal, Wood and Asphalt Surfaces

*Previene la oxidación  
Para uso en las superficies metálicas, maderas y de asfalto*

202



## FIBER-GUARD® HEAVY DUTY FIBERED Roof Coating



COMPLIANCE: • Miami-Dade Approved  
• ASTM D 4479  
• Asbestos Free

Rejuvenates Worn Surfaces  
Fiber Reinforced for Increased Durability

*Rejuvenece la superficies desgastadas  
Reforzado con fibra para un aumento en durabilidad*



# EMULSION BASED COATINGS

RECUBRIMIENTOS CON BASE DE EMULSIÓN



300



## NON-FIBERED Asphalt Emulsion



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved  
• ASTM D 1227  
• Asbestos Free


Ideal for Use in Cold Process Roofing  
Use with Polyester or Chopped Glass

*Ideal para uso en el techado de proceso frio  
Utilice con poliéster y vidrio cortado*

302



## FIBERED Asphalt Emulsion



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved  
• ASTM D 1227  
• Asbestos Free


Great for Maintaining Roofs in Good Condition  
Excellent Base Coat for Reflective Coatings

*Excelente para mantener los techos en buenas condiciones  
Recubrimiento de base excelente para recubrimientos  
reflectivos*

337



## ELASTOMERIC Asphalt Emulsion



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved  
• Exceeds ASTM D 1227  
• Asbestos Free

Ideal for Metal Roofs or Roofs With Movement  
Excellent for Use in Waterways and Prior to Reflective Coatings

*Ideal para techos de metal o techos con movimiento  
Excelente para uso en vias fluviales antes de aplicar los  
recubrimientos reflectivos*

# SPECIALTY SECTION

SECCIÓN DE ESPECIALIDADES

385



## INSUL-GRIP® RUBBER MODIFIED Insulation Adhesive



COMPLIANCE: • Asbestos Free

Ideal for All Rigid Insulation Boards  
Light Trowel Grade with Great Bonding Strength

*Ideal en los tableros rígidos de aislamiento  
Calidad liviana de uso con paleta con gran fuerza de unión*

525



## ARMORFLEX® THERMOPLASTIC Surfacing Compound



COMPLIANCE: • UL Class A Rated • Miami-Dade Approved  
• Exceeds ASTM D 3019 • Asbestos Free  
• SCAQMD Compliant Version Available

Withstands Ponding Water  
Ideal for Waterproofing BUR, Coal Tar Modified, & Gravel Roofs

*Resiste la acumulación de agua  
Ideal para la impermeabilización de techos BUR, de brea de  
carbón y de grava*

\*Citrus Version Available

# ▼ WATERPROOFING & DAMPPROOFING PRODUCTS

PRODUCTOS PARA IMPERMEABILIZACION

300



## NON-FIBERED Asphalt Emulsion



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved • ASTM D 1227  
• Asbestos Free


Great for Below-Grade Dampproofing  
Ideal for Cement Block and Concrete Surfaces

*Revestimiento asfáltico para techo y cimientos  
Ideal para bloques de cemento y superficie de concreto*

302



## FIBERED Asphalt Emulsion



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved • ASTM D 1227  
• Asbestos Free

Great for Below-Grade Dampproofing  
Ideal for Cement Block and Concrete Surfaces

*Revestimiento asfáltico para techo y cimientos  
Ideal para bloques de cemento y superficie de concreto*

305



## DAMPPROOFING Mastic



COMPLIANCE: • ASTM D 1227, Class I  
• Asbestos Free

Thick Trowel Grade, Emulsion-Based Mastic  
Ideal for Below Grade Dampproofing

*Masilla de calidad gruesa aplicada con paleta  
Ideal para impermeabilización en cimientos*

365



## ETERNA-FLASH® ALL WEATHER/SEASON SBS Flashing Cement



COMPLIANCE: • Miami-Dade Approved  
• ASTM D 6511 • ASTM D 4586  
• Fed Spec. SS-C-153C • Asbestos Free

Highly Rubberized Solvent-Based Mastic  
E-Z Spread Trowel Grade Formula

*Masilla basada en un solvente altamente modificado con ule  
Formula facil de aplicar*



## Bridge-Dek

Sheet Size: 4' x 8'  
Panel Thicknesses: 1/8", 1/4", 3/8", 1/2"

COMPLIANCE: • ASTM E 96  
• Zero Perm  
• Meets all IREM Standards

Ideal for Use in Bridge and Railway Construction  
Protects Waterproofing Membrane from Puncture

*Ideal para uso en la construcción de puentes y  
líneas ferroviarias  
Protege contra perforaciones en  
membranas impermeabilizadoras*



## Protection Panels

Sheet Size: 4' x 8', other sizes available  
Panel Thicknesses: 1/4", 3/8", 1/2", 1"

COMPLIANCE: • ASTM D 2643  
• ASTM E 96 Method BEBW  
Rated 0.000 grains/hr/sq. ft.  
Water Vapor Transmission  
• ASTM D 147 • ASTM D 154  
• ASTM D 994 • ASTM D 517  
• Zero Perm Rating

Great as a Re-Cover Board & Below-Grade System Protector  
Won't Rot or Degrade & Impervious to Water

*Excelente como tablero de recubierto y para proteger los  
sistemas debajo del nivel del suelo  
No se deteriorará ni se degenerará y es impermeable a  
la humedad*



# COOL ALUMINUM COATINGS

RECUBRIMIENTOS FRESCOS DE ALUMINIO



207



## SILVER GUARD-NF® NON-FIBERED Aluminum Roof Coating



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved  
• ASTM 2824 Type I • Asbestos Free

Bright Silver Protective Coating  
Meets ENERGY STAR Requirements

*Recubrimiento protector color plata brillante  
Cumple con los requisitos ENERGY STAR*

208



## SILVER GUARD-F® FIBERED Aluminum Roof Coating



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved  
• ASTM 2824 Type III • Asbestos Free

Bright Silver Fibered Protective Coating  
Meets ENERGY STAR Requirements

*Recubrimiento protector con fibra color plata brillante  
Cumple con los requisitos ENERGY STAR*

211



## LIQUID SILVER-NF® NON-FIBERED Aluminum Roof Coating



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved  
• ASTM 2824 Type I • Asbestos Free

Highly Reflective & Cool Silver Finish (Exceeds ENERGY STAR)  
Ideal for BUR, Metal & Modified Membranes

*Acabado plateado altamente reflejante y fresco  
(excede los requisitos ENERGY STAR)  
Ideal para las membranas BUR, de metal y modificadas*

212



## LIQUID SILVER-F® FIBERED Aluminum Roof Coating



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved  
• ASTM 2824 Type III • Asbestos Free

Highly Reflective & Cool Silver Finish (Exceeds ENERGY STAR)  
Ideal for BUR, Metal and Modified Membranes

*Acabado plateado altamente reflejante y fresco  
(excede los requisitos ENERGY STAR)  
Ideal para las membranas BUR, de metal y modificadas*

213



## SPEC-GRADE Aluminum Roof Coating



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved  
• ASTM 2824 Type I • Asbestos Free

Maximum Reflectivity & Coolest Finish (Exceeds ENERGY STAR)  
Ideal for BUR, Metal and Modified Membranes

*Acabado plateado sumamente reflejante y fresco  
(excede los requisitos ENERGY STAR)  
Ideal para las membranas BUR, de metal y modificadas*

\*Special Order Only

214



## SPEC GRADE FIBERED Aluminum Roof Coating



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved  
• ASTM 2824 Type III • Asbestos Free

Maximum Reflectivity & Coolest Finish (Exceeds ENERGY STAR)  
Ideal for BUR, Metal and Modified Membranes


*Acabado plateado sumamente reflejante y fresco  
(excede los requisitos ENERGY STAR)  
Ideal para las membranas BUR, de metal y modificadas*

\*Special Order Only

400



## SUNBRITE® Aluminum Emulsion Coating



COMPLIANCE: • UL Class A Rated  
• Miami-Dade Approved  
• ASTM D 6848 • Asbestos Free

Highly Reflective and Easier Application  
Ideal for BUR, Metal and Modified Membranes

*Altamente reflejante y la aplicación más fácil  
Ideal para las membranas BUR, de metal y modificadas*

# ▼ COOL ACRYLIC REFLECTIVE COATINGS

RECUBRIMIENTOS ACRÍLICOS REFLEJANTES Y FRESCOS

232



## INSTA-KOTE® MB Elastomeric Roof Coating



COMPLIANCE: • Energy Star  
• CRRC Listed • Title 24  
• Miami-Dade Approved  
• ASTM D 6083 • Asbestos Free


Ideal Base Coat with Exceptional Adhesion  
Prevents Bleed Through

*Es ideal como recubrimiento de base con una adherencia excepcional  
Previene exudación*

247



## SUNSHIELD® WHITE REFLECTIVE Elastomeric Roof Coating



COMPLIANCE: • Energy Star  
• CRRC Listed • Title 24  
• Asbestos Free


Elastic Roof Coating  
Extends Roof Life & Reduces Cooling Costs

*Recubrimiento elástico para techos  
Extiende la vida útil del techo y reduce el costo de enfriamiento*

248



## ARIZONA® -WHITE HIGH PERFORMANCE Elastomeric Roof Coating



COMPLIANCE: • Energy Star • CRRC Listed  
• Title 24 • UL Class A Rated  
• Miami-Dade Approved  
• ASTM D 6083 • Asbestos Free

Highly Reflective to Cool Roof Surfaces  
Helps Reduce Energy Usage & Extends Roof Life

*Altamente reflejante para enfriar las superficies de techos  
Ayuda reducir el uso de energía y a extender la vida útil del techo*

252



## SUNWHITE PREMIUM Elastomeric Roof Coating



COMPLIANCE: • Energy Star • CRRC Listed  
• Title 24 • UL Class A Rated  
• Miami-Dade Approved  
• ASTM D 6083 • Asbestos Free


Highest Reflectivity, Tensile and Elongation  
Drastically Reduces Roof Temperature and Cooling Costs

*La más alta reflectividad, extensibilidad y elongación  
Reduce radicalmente la temperatura del techo y los costos de la refrigeración*

257



## GRIP-IT® EPDM Surface Prep/Roof Cleaner



COMPLIANCE: • Asbestos Free


Rinsable Primer and Cleaner  
Must Be Used Before Coating EPDM Surfaces with #258

*Base y limpiador enjuagables  
Se debe usar antes de recubrir la superficie EPDM con #258*

258



## RE-NEW IT EPDM Rubber Coating



COMPLIANCE: • Energy Star • CRRC Listed  
• Title 24 • UL Class A Rated  
• Miami-Dade Approved  
• ASTM D 6083 • Asbestos Free

Ideal for EPDM Roof Surfaces  
Highly Reflective & Cool Coating

*Ideal para las superficies de techos EPDM  
Recubrimiento altamente reflejante y fresco*



**APOC, “Tested Best” by  
Independent Laboratory Analysis.**



# ▼ COOL ACRYLIC REFLECTIVE COATINGS

RECUBRIMIENTOS ACRÍLICOS REFLEJANTES Y FRESCOS



260



## AMAZ 'N STUFF® WHITE Elastomeric Roof Patch

3.5 1 U.S. GAL

COMPLIANCE: • Miami-Dade Approved • TAS 139  
• ASTM D 1475 • ASTM D 2938 • ASTM D 2196  
• ASTM G 26 • ASTM D 2939 • Asbestos Free

Highly Reflective Sealant and Patch  
Ideal for Use Before Acrylic and Emulsion Coating

*Sellador y parche altamente reflejante  
Ideal de uso antes de aplicar los recubiertos acrílicos y de emulsión*

273



## COOL-GRAY PREMIUM Elastomeric Roof Coating

TOTE 275 55 5 U.S. GAL

COMPLIANCE: • Energy Star • CRRC Listed  
• Title 24 • UL Class A Rated  
• Miami-Dade Approved  
• ASTM D 6083 • Asbestos Free

Exceptional Tensile Strength and Elongation  
Cool Gray Finish to Reduce Roof Temperature

*Resistencia excepcional a tracción y elongación  
Acabado gris para reducir la temperatura del techo*

\*Special Order Only / Solamente orden especial

274



## COOL-TAN PREMIUM Elastomeric Roof Coating

TOTE 275 55 5 U.S. GAL

COMPLIANCE: • Energy Star • CRRC Listed  
• Title 24 • UL Class A Rated  
• Miami-Dade Approved  
• ASTM D 6083 • Asbestos Free

Exceptional Tensile Strength and Elongation  
Cool Tan Finish to Reduce Roof Temperature

*Resistencia excepcional a tracción y elongación  
Acabado color café claro para reducir la temperatura del techo*

\*Special Order Only / Solamente orden especial



Church of the Nazarene

## ► The Cool Roof Experts™

APOC is a leader in environmental design and cool roof technology. With increasing population and soaring energy demand, cool roofs provide relief to a world filled with energy challenges.

As a charter member of the CRRC and the ENERGY STAR programs, APOC is committed to cool roofing and providing solutions to roofing contractors, building owners, facility managers and property management companies.



# ▼ THERMOPLASTIC COATINGS & SEALANTS

RECUBIERTOS Y SELLADORES TERMOPLÁSTICOS

501



## SUPERFLASH® NEOPRENE® Flashing Cement

3 1 U.S. GAL | TUBE

COMPLIANCE: • Exceeds Performance of ASTM D 4586  
• ASTM D 3409 • ASTM D 6511  
• Asbestos Free

Compatible with Virtually Any Roof Surface  
50 Year Durability & Watertight Guarantee

*Compatible con prácticamente cualquier superficie de techo  
Garantía de durabilidad y impermeabilidad de 50 años*

502



## BRUSHABLE NEOPRENE® Thermoplastic Sealant

3 1 U.S. GAL

COMPLIANCE: • Exceeds Performance of ASTM D 4479  
• ASTM D 6511  
• Asbestos Free

Brushable Self-Leveling Formula  
Compatible with Most Roof Surfaces

*Fórmula autoniveladora aplicable con brocha  
Compatible con prácticamente cualquier superficie de techo*

505



## ETERNA-PATCH® WHITE THERMOPLASTIC Flashing Sealant

3 1 U.S. GAL

COMPLIANCE: • Exceeds Performance of ASTM D 4479  
• ASTM D 6511  
• Asbestos Free

High Performance, Fast Cure Sealant  
Flexible, Durable, and Watertight

*Sellador de alto rendimiento  
Flexible, durable e impermeable*

525



## ARMORFLEX® THERMOPLASTIC Surfacing Compound

5 U.S. GAL

COMPLIANCE: • UL Class A Rated • Miami-Dade Approved  
• Exceeds ASTM D 3019 • Asbestos Free  
• SCAQMD Compliant Version Available

Withstands Ponding Water  
Ideal for Waterproofing BUR, Coal Tar Modified & Gravel Roofs

*Resiste la acumulación de agua  
Ideal para la impermeabilización de techos BUR, de brea de  
carbón y de grava*

\*Citrus Version Available

535



## LIQUID RUBBER Aluminum Roof Coating

5 U.S. GAL

COMPLIANCE: • ASTM D 2824  
• Asbestos Free

Heavy Duty Rubberized Aluminum Coating  
Ideal for Metal and Modified Roof Systems

*Recubrimiento de aluminio engomado de alta resistencia  
Ideal para los sistemas de techos metálicos y modificados*

545



## ETERNA-FLEX® WHITE THERMOPLASTIC Liquid Rubber Coating

5 U.S. GAL

COMPLIANCE: • Asbestos Free

Ultra Premium Liquid Rubber Coating  
Ideal for Metal, Single Ply\* and Other Roof Systems

*Recubrimiento de hule líquido de ultra primera calidad  
Ideal para los techos metálicos, techos de una capa y otros  
sistema de techos*

\*Check type and manufacturer



# ▼ APOC ACCESSORIES

ACCESORIOS APOC



483



## POLYESTER Reinforcing Fabric



3 oz./sq. yd.  
Available Widths: 40", 12", 6", 4"

Reinforces and Adds Strength and Durability  
Works with Emulsion and Solvent Systems

*Refuerza y agrega resistencia y durabilidad  
Trabaja con sistemas de emulsión y solventes*


570700



## 50 Lb. Fiberglass Roving

For Chopped Application Use  
Reinforces Emulsion Systems for Seamless Surfaces

*Se aplica con los sistemas basados en emulsiones  
Refuerza el recubrimiento para las superficies de techos  
sin costura*



## DEK-TOP® Walkway Pads

See Website for Additional Colors  
Sheet Size: 3' x 4' Panel Thicknesses: 1/2", 3/4", 1"

Protects Roof Membrane from Costly Damage  
Ideal Around Roof Hatches and HVAC Units

*Protege la membrana del techo de daños costosos  
Ideal alrededor de escotillas del techo y unidades HVAC*

\* Regional Availability

# ▼ SPRAY INFORMATION

INFORMACION SOBRE EL AEROSOL

APOC#	PRODUCT	Required P.S.I.	Spray Rate (GAL./MIN.)	Material Needed per 100 Sq. Ft.*	Tip Size
103	Fast Dry Asphalt Primer	100 - 500	(0.5-2.0)	(.25-1)	.019-.031
107	Fibrex® Cold Process Cement and Adhesive	2000 - 3000	(3-4)	(2)	.061-.080
136	Durabond™ MBA Elastomeric	2000 - 3000	(3-4)	(2)	.061-.080
202	Fiber-Guard™ Heavy Duty Fibered Roof Coating	Brush Grade	N/A	N/A	Brush Grade
207	Silver-Guard NF™ Non-Fibered Aluminum Roof Coating	1000 - 1500	(1.5-2.0)	(.5-2)	.040-.055
208	Premium Fibered Aluminum Roof Coating	1500 - 2000	(1.5-2.0)	(1-2)	.055-.061
211	Premium Non-Fibered Aluminum Coating	1000 - 1500	(1.5-2.0)	(1-2)	.040-.055
212	Fibered Aluminum Roof Coating	1500 - 2000	(1.5-2.0)	(1-2)	.055-.061
232	Insta-Kote™ MB Elastomeric Roof Coating	2000 - 3000	(1-3)	(1.5)	.030-.041
248	Arizona®-White High Performance Elastomeric Roof Coating	2000 - 3000	(1-3)	(1.5-3)	.030-.041
252	Sunwhite Premium Elastomeric Roof Coating	2000 - 3000	(1-3)	(1.5-3)	.030-.041
258	Re-New It EPDM Rubber Coating	2000 - 3000	(1-3)	(1.5-3)	.035-.047
300	Non-Fibered Asphalt Emulsion	1000 - 1500	(3-6)	(2-4)	.061-.099
302	Fibered Asphalt Emulsion	Brush Grade	N/A	N/A	Brush Grade
337	Elastomeric Asphalt Emulsion	1000 - 1500	(3-6)	(2-4)	.061-.099
400	Sunbrite™ Aluminum Roof Coating	500 - 1000	(2)	(1-2)	.040-.061
545	Eterna-Flex™ White Thermoplastic Liquid Rubber Coating	2000 - 3000	(2)	(.5-2)	.030-.047

Variables: • Temperature of product • Distance from pump to point of application • Hose size • Running two guns off one hose • Ambient air temperature

\* See Specification for Recommended Application.

For More Information, go to [www.apoc.com](http://www.apoc.com)

Como técnicos estamos para contestar y  
ayudarlos en todas sus preguntas

**APOC**

A Division of Gardner Industries

Corporate Headquarters

P.O. Box 5449

Tampa, FL 33675

East Coast

(813) 248-2101

West Coast

(562) 423-6471

▶ **The Roof Restoration Experts™**

