

MATERIAL SAFETY DATA SHEET

Date REVISED 04/19/07

SECTION I

MANUFACTURERS NAME

APOC

STREET ADDRESS

4161 E 7TH AVENUE

EMERGENCY TELEPHONE NUMBER

1-800-424-9300

PRODUCT CLASS

ASPHALT CLAY FILLER COAT

CITY, STATE, AND ZIP CODE

TAMPA, FL 33605

MANUFACTURER'S CODE

IDENTIFICATION

APOC 330

TRADE NAME

APOC

SECTION II- HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV PPM	TLV Mg/M3	LEL	VAPOR PRESSURE
PETROLEUM ASPHALT CAS # - 8052-42-4	<45%		5		
CLAY STABILIZER CAS #- 1332-58-7	<10%	**	2*		
WATER CAS #- 7732-18-5	>50%	*			
CELLULOSE FIBER CAS #- 9004-34-6	<5%		10		

ADDITIONAL INFORMATION-*AS RESPIRABLE FRACTION OF DUST.

Hazardous Materials Identification System (HMIS)

Health
1

Flammability
0

Reactivity
0

Personal Protection
C

SECTION III – PHYSICAL DATA

BOILING RANGE: 200°F - 220°F VAPOR DENSITY HEAVIER LIGHTER, THAN AIR

EVAPORATION RATE FASTER SLOWER, THAN
ETHER PERCENT VOTILE BY VOLUME <45 % WEIGHT PER GALLON
BY VOLUME 8.5 LBS

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY - N/R

FLASH POINT- N/A

EXTINGUISHING MEDIA-DRY CHEMICAL, CO2

UNUSUAL FIRE AND EXPLOSION HAZARDS- NONE

SPECIAL FIRE FIGHTING PROCEDURES- USE STANDARD FIRE FIGHTING PROCEDURES

SECTION V – REACTIVITY DATA

STABILITY: UNSTABLE

STABLE

CONDITIONS TO AVOID: HEAT, FLAMES, STRONG OXIDIZERS

INCOMPATIBILITY (MATERIALS TO AVOID): CARBON OXIDES

HAZARDOUS DECOMPOSITION PRODUCTS: NONE

HAZARDOUS POLYMERIZATION: MAY OCCUR

WILL NOT OCCUR

CONDITIONS TO AVOID: NONE

SECTION VI-HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE-ACUTE: SKIN: PROLONGED /REPEATED CONTACT MAY CAUSE IRRITATION. - EYES: MAY CAUSE SLIGHT IRRITATION. -INGESTION MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ).

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Read and follow label directions and information given on Material Safety Data Sheets and use care when handling or using all petroleum products.

EMERGENCY FIRST AID PROCEDURE-SKIN: REMOVE CONTAMINATED CLOTHING. WASH EXPOSED AREA WITH SOAP AND WATER. IF IRRITATION PERSISTS GET MEDICAL ATTENTION. EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. KEEP PERSON WARM AND QUIET. GET MEDICAL ATTENTION.

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ELIMINATE SOURCES OF IGNITION KEEP PRODUCT OUT OF SEWERS BY DIKING OR IMPOUNDING. SOAK UP SPILL WITH SAND OR OTHER ABSORBENT. PLACE IN CONTAINERS. WASH AREA.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL REGULATIONS.

SECTION VIII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: USE NIOSH/MSHA APPROVED RESPIRATOR WHEN TLV IS EXCEEDED.

VENTILATION: USE IN WELL VENTILLATED AREAS.

PROTECTIVE GLOVES: USE HEAVY RUBBER

EYE PROTECTION: SPLASH RESISTANT GOGGLES

SECTION IX – REGULATORY INFORMATION

ALL INGREDIENTS IN THIS PRODUCT ARE TSCA LISTED

U.S. FEDERAL REGULATIONS: THIS PRODUCT HAS NOT BEEN CLASSIFIED A CARCINOGEN BY THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA), THE NATIONAL TOXICOLOGY PROGRAM (NTP) OR THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC).