



COMPLIANCE: Exceeds performance requirements of ASTM D517 and ASTM E108.

DESCRIPTION: APOC® 5040 Dek-Top® Walkway Pads have a long-life, are trouble free and non-skid. DEK-TOP pads are made of asphalt, reinforcing fibers and mineral fillers. The pads are compressed and molded under heat between inorganic fiberglass mats, top and bottom. Ceramic granule surfacing adds attractive color options and skid-resistance. Use of DEK-TOP applied on BUR and modified bitumen membranes, provides a safe and attractive walkway for access to roof-top equipment, signs, etc., by maintenance personnel, roofing crews and other trades that require access to the roof. DEK-TOP has also been used for roof-top running tracks, solar panel platforms, satellite platforms, and under sleepers for wood decks and small HVAC units.

PREPARATION: Sweep roof surface free of debris, dirt and dust. All gravel must be spudded clean on existing gravel surfaced roofs where DEK-TOP is to be applied. On new BUR install directly to the top ply. On cap sheets, Modified SBS and APP apply directly to the capsheet surface.

APPLICATION: For exterior use only. Chalk line walkways where DEK-TOP pads are to be installed. This will help the installers applying adhesive and act as a guide to insure a straight and true installation. Sweep clean the underside of the DEK-TOP pad, back-mop pad and then set pad in a flood coat of hot asphalt. APOC plastic or flashing cement may be used as an alternate adhesive to hot asphalt. Allow 2" to 4" spacing between pads for roof drainage. Use a utility knife to cut and fit around roof top units and pipe penetrations.

PRECAUTIONS: DEK-TOP by itself is not intended to provide a finished roof membrane or intended as a substitution for roofing or to provide any structural support. DEK-TOP is not typically recommended for patio balconies or plaza decks where high point loading from furniture legs and high heels could wear away the surface.

Dimensions	Weight	Surface Color
1/2" 3' X 4'	45 lbs (approx)	White ceramic granules
3/4" 3' X 4'	70 lbs (approx)	White ceramic granules
1" 3' X 4'	85 lbs (approx)	White ceramic granules

Note: Other granule colors available upon request.

HANDLING PRECAUTIONS: Product safety information required for safe use is not included. Before handling, read product safety data sheets and container labels for safe use and for physical and health hazard information. Safety Data Sheets are available on the APOC website at www.apoc.com. You can also obtain a copy from your local APOC Distributor or APOC sales representative.

LIMITED WARRANTY AND DISCLAIMER: To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact APOC to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with APOC warranty procedures and program.

For limited warranty and disclaimer information, visit our website at: www.apoc.com/productwarrantyinfo.

©2010 Gardner-Gibson, Inc.
Manufactured by / Fabricado por:
Gardner-Gibson, Inc.
P.O. Box 5449, Tampa, FL 33675

See SDS for more info

