

AP 202



FIBERED ROOF & FOUNDATION COATING Data Sheet

COMPLIANCE: Exceeds performance requirements of ASTM D 4479. MIAMI-DADE APPROVED. ASBESTOS FREE.

DESCRIPTION: APOC® 202 Fibered Roof & Foundation Coating is a tough, heavy duty, professional grade coating. It is formulated with select asphalt, solvent and fibers to provide a durable barrier over existing roof and below grade surfaces. APOC® 202 can be applied over built-up, composition and metal roofs, as well as concrete and masonry foundations and walls. It is ideal for use as a component in below grade waterproofing and dampproofing systems.

PREPARATION: All surfaces must have proper drainage and be clean, dry and free of surface rust and any other foreign matter. Repair all problem areas with an approved APOC Cement. MIX THOROUGHLY. DO NOT HEAT OR THIN. DO NOT APPLY IF RAIN IS EXPECTED WITHIN 24 HOURS.

FOR BEST RESULTS: Apply on clear sunny day when surface temperatures are between 35° and 120°F. For temperatures below 50° product should be stored in heated room (65° to 90°F.) at least 24 hours prior to application. We also highly recommend application of a reflective coating after a minimum of 45 days cure time. This will greatly extend the life of the roof.

APPLICATION: For exterior use only. Apply using a brush or 1/2" to 3/4" nap roller. Form a thin and continuous film. Avoid heavy mounds of mass accumulation. Coverage rates 1-1.5 gallons per 100 sq. ft. over concrete and masonry surfaces and 1 gallon per 100 sq. ft. over smooth or built-up roofs. For above and below grade foundations ensure all pin holes are filled with coating; apply second coat at right angles to first coat. For waterproofing systems and applications, contact manufacturer for written requirements & specifications. Allow minimum of 6 hours between coats and at least 36 hours drying time prior to backfilling. Do not apply to roofs with slopes greater than a 1/4" per foot.

PRECAUTIONS: This product contains solvents. When working around ventilation units or HVAC equipment, ensure proper fume mitigation procedures are taken to avoid fumes and / or odors from entering air handling equipment and building. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110° F. This manufacturer also disclaims liability for flat surface application where poor drainage or moisture may prevail. Do not reuse empty containers. Do not use in drinking water or food systems. Seal container when not in use.

CLEAN-UP: Clean tools with paint thinner or mineral spirits.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

| | |
|--------------------------|--------------------------------|
| Weight Per Gallon | 8.5-9.0 lbs. |
| Residue by Evaporation | 76 min. |
| Consistency | Brush |
| Application Temperatures | 50° - 120°F |
| Clean-up Tools | Paint Thinner, Mineral Spirits |

Approx. Shipping Weights: (Note: All approx. weights include container.)

| | |
|-------------------|---------|
| 5 gallons (18.9L) | 48 lbs. |
| 55 drums (208.2L) | 510 lbs |

CAUTION – COMBUSTIBLE MIXTURE CAUTION!: HARMFUL OR FATAL IF SWALLOWED. EYE, SKIN AND RESPIRATORY IRRITANT.

Contains Petroleum Distillate. Keep away from heat, sparks and open flame. If swallowed DO NOT induce vomiting. Call physician immediately. In case of : Eye contact - flush with large amounts of room temperature water for 15 minutes; Skin contact - wash thoroughly with soap and water; Irregular or stopped breathing - administer oxygen, give artificial respiration and get medical attention immediately. Avoid prolonged breathing of vapor or spray mist.

**FOR EXTERIOR USE ONLY
Use with adequate Ventilation
Keep Out of Reach of Children
VOC/VOS - 250 g/l max. (2.1 lbs./gal.)**

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation, when using product.

WARRANTY AND DISCLAIMER: To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact APOC to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with APOC warranty procedures and program.

For limited warranty and disclaimer information, visit our website at: www.apoc.com/productwarrantyinfo.

©2009 Gardner Asphalt Corporation Manufactured by / Fabricado por: Gardner Asphalt Corporation P.O. Box 5449, Tampa, FL 33675



See MSDS for more info



Gardner Asphalt Corporation • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101 • Fax (813) 248-6768 • www.apoc.com