



UBQ Industries

Technical Data Sheet (TDS)- Active Elements – Dilute

Use Active Elements – Dilute to achieve a lighter shade of Concrete Acid Stain color. With Active Elements – Dilute blend of proprietary enhancers, your Concrete Acid Stain will maintain vivid tones when diluting for lighter shades. Dilute keeps the correct chemical balance to let the Concrete Acid Stain open the pores of the concrete floor and deliver color.

*****For use with Concrete Acid Stain Only!!!**

PRODUCT USE: Mix 1-3 parts Active Elements – Dilute with Concrete Acid Stain when diluting for lighter shades of color. Apply a test sample of the diluted stain in an inconspicuous area of the floor to verify the color. It is advised to use the same application method for the test spot as what is planned for the entire floor.

Do not exceed 3 Parts Active Elements – Dilute per 1 part Concrete Acid Stain.

SAFETY: Always use appropriate safety equipment including but not limited to, goggles, face shield, rubber gloves, chemical resistant clothing or apron, and chemical respirator. Do not permit contact with eyes or skin. Do not breathe vapors, ventilate area during mixing and application. Close container immediately after each use. Store upright in a tightly closed container away from combustible material and sources of heat. Never transfer to an unmarked container. Do not reuse empty container, empty containers may contain hazardous product residues. Before use, review the Material Safety Data Sheet for further information, including health effects.

FIRST AID

Skin - Wash thoroughly with soap and water. Discard affected clothing and footwear.

Eyes - Flush with water immediately. Hold eyelids apart while flushing material out thoroughly with large amounts of water. Seek Medical Attention Immediately!

Ingestion - Give several glasses of water. Seek Medical Attention Immediately!

Inhalation - Move to fresh air.

Warranty

This warranty is made in lieu of all other warranties, either expressed or implied. Before application the User shall determine the suitability of the product for his/her intended use and User assumes all risks and liabilities whatsoever in connection therewith. Neither seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The Manufacturer and/or Seller warrants that if any goods supplied prove defective in material the sole obligation shall be to replace said product. Any claim of defective product must be received in writing within one (1) year from date of shipment. Neither Manufacturer nor Seller shall assume any liability for injury, loss, or damage resulting from use of this product.

DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.