



UBQ Industries

Technical Data Sheet (TDS) - Active Elements – Liquid Stamp Release

Active Elements – Liquid Stamp Release is a clear release to be used when stamping, texturing, or imprinting concrete, overlay, and vertical coating systems. It acts as a temporary bond breaker for your imprinting tools.

- Safe to use on uncolored and integral-colored surfaces.
- Safe for use on vertical systems
- Active Elements - Liquid Stamp Release evaporates completely without leaving residue.
- Lubricates texturing tools for a longer life span.
- The clear release allows for immediate project inspection.
- A much cleaner alternative to powder-release agents.
- Prevents concrete and overlay build-up on tools.

APPLICATION

When the surface is ready for imprinting, spray a uniform layer of Active Elements – Liquid Stamp Release on imprinting tools and project surface. It may be necessary to reapply often during windy and/or hot conditions.

Avoid “puddling” of Active Elements – Liquid Stamp Release on the surface.

DO NOT incorporate or trowel Active Elements – Liquid Stamp Release into the wet/plastic concrete, overlay, or vertical mix.

All sprayer equipment used for Active Elements – Liquid Stamp Release application must be industrial grade solvent resistant rated.

COVERAGE

150-250 square feet per gallon. Coverage variations depend on the type of imprinting operation, ambient conditions, and type of sprayer being used.

SAFETY

Always wear proper safety equipment such as goggles, gloves, respirator, and protective clothing. Use only in well-ventilated areas.

CLEAN UP

Clean tools with soap and water after use.

Warranty

This warranty is made in lieu of all other warranties, either expressed or implied. Before application the User shall determine the suitability of the product for his/her intended use and the User assumes all risks and liabilities whatsoever in connection therewith. Neither seller nor manufacturer has any knowledge or control concerning the purchaser’s use of this product and no warranty is made as to the results of any use. The Manufacturer and/or Seller warrants that if any goods supplied prove defective in material the sole obligation shall be to replace said product. Any claim of defective product must be received in writing within one (1) year from the date of shipment. Neither the Manufacturer nor the Seller shall assume any liability for injury, loss, or damage resulting from the use of this product.

DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.