

# Technical Data Sheet (TDS)

## Active Elements – Degrease

[www.UBQind.com](http://www.UBQind.com)

### Exterior General Cleaning

Spray Active Elements - Degrease on the concrete and scrub with a broom, then rinse with pressure washer.

### Interior General Cleaning

Spray Active Elements - Degrease on the concrete and scrub using a floor machine (buffer).

### Oil Spots

Saturate the affected area with Active Elements - Degrease and scrub with a stiff bristle brush, then pressure wash. Repeat as necessary to remove the oil on the surface. Note: On many oil spots a shadow of the oil spot will still remain even after several treatments. It is important to clean the oil spot until it no longer repels water.

### After Stripping Paint and Sealers

After using Active Elements - Paint Strip to remove paint or sealer, spray a liberal amount of Active Elements - Degrease on the floor and scrub with a floor machine (buffer) using a nylon bristle brush attachment, black pad or sanding screen. This process is imperative to remove residual oils and debris that may inhibit the ability of stain to react or penetrate.

### Storage

Do not allow to freeze.

Keep away from children.

### Safety

Eye and skin irritant

Do not breathe vapors. When using in confined or limited ventilation areas, use appropriate respirator to protect against breathing vapors. Avoid contact with skin; wear protective gloves and clothing. Always use eye protection such as goggles, face shield or safety glasses. Read Material Safety Data Sheet before using.

### First Aid

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Seek medical attention.

Skin Contact: Immediately remove contaminated clothing. Wipe excess from skin and wash with soap and water. Seek medical attention if irritation persists.

Inhalation: Remove person to fresh air and provide oxygen if breathing is difficult. Seek medical attention.

### Warning

Do not mix with any other chemicals as hazardous gases may result.

Do not allow Active Elements - Degrease to dry on stained or sealed surfaces.

### Warranty

This warranty is made in lieu of all other warranties, either expressed or implied. Before application the User shall determine the suitability of the product for his/her intended use and User assumes all risks and liabilities whatsoever in connection therewith. Neither seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The Manufacturer and/or Seller warrants that if any goods supplied prove defective in material the sole obligation shall be to replace said product. Any claim of defective product must be received in writing within one (1) year from date of shipment. Neither Manufacturer nor Seller shall assume any liability for injury, loss, or damage resulting from use of this product.

DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.