

# Technical Data Sheet (TDS)

## Active Elements – Liquid Release “Monkey Farts”

[www.UBQind.com](http://www.UBQind.com)

Active Elements – Liquid Release is a clear release to be used when stamping, texturing or imprinting concrete, overlay and vertical coating systems. It acts as a temporary bond breaker for your imprinting tools.

- Awesome “Monkey Farts” fragrance
- Safe to use on uncolored and integral colored surfaces.
- Safe for use on vertical systems
- Liquid Release evaporates completely without leaving residue.
- Lubricates texturing tools for longer life span
- Clear release allows for immediate project inspection.
- Much cleaner alternative to powder release agents.
- Prevents concrete and overlay build up on tools

### **Application:**

When surface is ready for imprinting, spray a uniform layer of Liquid Release on imprinting tools and project surface. It may be necessary to reapply often during windy and/or hot conditions.

Avoid “puddling” of Liquid Release on the surface.

DO NOT incorporate or trowel Liquid Release into the wet/plastic concrete, overlay or vertical mix.

All sprayer equipment used for Liquid Release application must be industrial grade solvent resistant rated.

### **Coverage:**

150-250 square feet per gallon. Coverage variations depend on type of imprinting operation, ambient conditions and type of sprayer being used.

### **Safety:**

Always wear proper safety equipment such as goggles, gloves, respirator and protective clothing. Use only in well ventilated areas.

### **Clean Up:**

Clean tools with soap and water after use.

### **Warranty**

This warranty is made in lieu of all other warranties, either expressed or implied. Before application the User shall determine the suitability of the product for his/her intended use and User assumes all risks and liabilities whatsoever in connection therewith. Neither seller nor manufacturer has any knowledge or control concerning the purchaser’s use of this product and no warranty is made as to the results of any use. The Manufacturer and/or Seller warrants that if any goods supplied prove defective in material the sole obligation shall be to replace said product. Any claim of defective product must be received in writing within one (1) year from date of shipment. Neither Manufacturer nor Seller shall assume any liability for injury, loss, or damage resulting from use of this product.

DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.