

C.SCOPE

DESIGNED &
MANUFACTURED IN

**GREAT
BRITAIN**

The C.SCOPE 4MXi delivers sharp and fast signal response with a lightning recovery time

The CS4MXi operates on the famed C.Scope 17kHz frequency operating system developed by C.Scope together with detector enthusiasts specifically for European and UK soil and mineralisation types.

Benefitting from new generation signal processing and filtering the 4MXi produces a superb **sharp and fast signal response with a lightning recovery time.**

The **CS4MXi** features the option of **three interchangeable heads to enable deeper detection, greater ground coverage and optimised performance for a variety of situations.**

Two of these are 2D elliptical and one concentric. The CS4MXi is supplied as standard with the 8 x 11" elliptical search head.

Check out the deals on extra heads – you will be surprised how generous we can be.

The CS4MXi has an **Auto and Variable Ground Exclude Control** for more precise ground elimination on mineralised sites.

The CS4MXi has **Two Discriminate Controls** for an instant comparison and analysis of signals.

Discriminate 1 can be set low to eliminate iron and Discriminate 2 set high to still accept small hammered silver. There is also a **Pinpoint Function** which switches off the motion effect so that the search head can be brought to rest over the exact target location.

“Plenty of people say they prefer the C.SCOPE ‘Motion’ detectors to machines 3 times the price...”

“You will be amazed that such depth and sensitivity can come with such a reasonable price tag”.

FREE

UK mainland
delivery for all online
detector orders



DESIGNED &
MANUFACTURED IN
**GREAT
BRITAIN**

*Designed and manufactured in the UK -
the quality, ruggedness and perfect lightweight balance
of a C.SCOPE detector is second to none.
This quality is allied to C.Scope's legendary
customer service and an unequalled warranty.*



CS4MXi SPECIFICATION

WEIGHT 1.45 kg including batteries

FREQUENCY 17 kHz

MODE Motion

On/Off Sensitivity
Two channel discrimination adjustable settings
Default Auto Ground Balance setting
Manual adjustable Ground Balance setting
Pinpoint switch.

POWER 8 Alkaline 1.5 volt AA or rechargeable NiMH pack.
Battery life approximately 50 hours.
Waterproof sealed battery compartment with easy fit large
knurled nut locking.

INTERCHANGEABLE LIGHTWEIGHT SEARCH HEADS
8" (20cm) concentric - available as OPTION
8 x 11" (20 x 28cm) elliptical 2D - supplied as STANDARD
11 x 14" (28 x 34cm) elliptical 2D - available as OPTION

CONTROL BOX in rugged pressure tested ABS moulding.
Hipmount facility.

TWO PART STEM with cam knurled nut locking and hole and
pin alignment and length adjustment. GRP lower stem with
ultra strong bolt to the search head.



Socket & Plug connector
for NEW interchangeable
search heads.

*Designed and manufactured in the UK -
the quality, ruggedness and perfect lightweight balance
of a C.SCOPE detector is second to none.
This quality is allied to C.Scope's legendary
customer service and an unequalled warranty.*



20cm Polo

20 x 28cm 2D
(as standard)

20 x 34cm 2D

cscopemetaldetectors.com

C.SCOPE International Ltd

Kingsnorth Technology Park, Wotton Road, Ashford, Kent TN23 6LN

Tel. 01233 629181 email info@cscope.co.uk