

DESIGNED & MANUFACTURED GREAT BRITAIN



The C.SCOPE 6MXi

The Specialist 'Motion' detector

The CS6MXi is a specialist 'MOTION' detector featuring the famed C.SCOPE Audio Tone Discrimination feature. This advanced multi tone discrimination allows the user to detect the smallest and thinnest coins in the most heavily contaminated or mineralised sites. The 6MXi uses the latest microprocessor power to sift through, filter and then analyse the target signals from the ground, giving maximum performance and saving you valuable detecting time.

The **CS6MXi** features an extremely fast 17kHz response and recovery time with a crisp clear signal.

The **Three Pitch Audio Discrimination** allows easy identification of targets before even thinking about digging. A high pitch signal tells you it's time to dig.

The Variable Discrimination Control allows further target analysis and the ability to identify and reject foil type signals. If you are not interested in iron, you can decrease the **Iron Volume** level and eliminate these signals altogether meaning the CS6MXi is always at its optimum level of tuning.

The CS6MXi signal is a real time instantaneous signal which combined with the Iron Volume and **Discriminate Volume** settings give you clear, fast and precise speed of analysis on every find. There is also a **Pinpoint Function** which switches off the motion effect so that the search head can be brought to rest over the exact target location.

Every experienced detectorist has a favourite site that was once a thriving, bustling lived in location.

These are the sites that tell us most about our fascinating history.

These sites are the most challenging and difficult. The C.Scope 6MXi is designed as a specialist detector for these special sites.

FREE

UK mainland delivery for all online detector orders





CS6MXi SPECIFICATION

WEIGHT 1.45 kg including batteries

FREQUENCY 17 kHz

MODE Motion

On/Off Sensitivity

Discrimination adjustable setting

Multi tone discrimination in all metal mode

Microprocessor filtering, analysis and processing of signals Iron Volume

Disc Volume

Default Auto Ground Balance setting

Manual adjustable Ground Balance setting

Pinpoint switch.

POWER 8 Alkaline 1.5 volt AA or rechargeable NiMH pack. Battery life approximately 30 hours.

Waterproof sealed battery compartment with easy fit large knurled nut locking.

INTERCHANGEABLE LIGHTWEIGHT SEARCH HEADS

8" (20cm) concentric - available as OPTION 8 x 11" (20 x 28cm) elliptical 2D - supplied as STANDARD

11 x 14" (28 x 34cm) elliptical 2D - available as OPTION

CONTROL BOX in rugged pressure tested ABS moulding. Hipmount facility.

TWO PART STEM with cam knurled nut locking and hole and pin alignment and length adjustment. GRP lower stem with ultra strong bolt to the search head.

Designed and manufactured in the UK the quality, ruggedness and perfect lightweight balance of a C.SCOPE detector is second to none. This quality is allied to C.Scope's legendary customer service and an unequalled warranty.









20 x 28cm 2D (as standard)

20 x 34cm 2D

cscopemetaldetectors.com

C.SCOPE International Ltd Kingsnorth Technology Park, Wotton Road, Ashford, Kent TN23 6LN Tel. 01233 629181 email info@cscope.co.uk