



# PAVER SEALER

## Description

A water-based, penetrating concrete paver and natural stone sealer that forms an invisible barrier that protects against oil and water-based stains.

## Features

- Excellent Stain Protection
- Water Based
- Natural Look
- Safe and Easy to Use
- Low Odor
- VOC Compliant
- Interior and Exterior

## Recommended Surface Types

Concrete pavers. Natural stone, including granite, marble, slate, limestone, travertine, sandstone, bluestone, Saltillo and other clay-based tile.

## Coverage

Up to 350 sq. ft. per gallon for a single coat depending on surface type and texture.

## Expected Wear

Up to 3 years.

## Available Sizes

1 Gallon, 5 Gallon

## Technical Information

VOC Content: 60 g / L including water (Low Solids Coating)

Cure Time: 24 hours

Foot Traffic: 6 hours after final application

## Emergency / First Aid Procedures

IF INHALED: Get medical advice/attention if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. If irritation (redness, rash, blistering) develops, get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation develops and persists, get medical attention. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

**EMERGENCY HOT LINE: 800-222-1222**

## Contact Information

MORE™ Surface Care, LLC  
Palo Alto, California, USA  
844-404-MORE (6673)  
www.moresurfacecare.com

## Storage and Handling

WARNING: Harmful if inhaled. Do not aerosolize. Keep out of reach of pets and children. Avoid contact with skin and eyes. Wear protective gloves/eye protection. Minimize exposure to vapors. Use in a well-ventilated area. Dispose of unused product in accordance with local laws and guidelines. DO NOT allow to freeze. DO NOT mix with other chemicals.

## Usage Instructions

1. Read entire label before using and use only as directed.
2. Surface should be dry, clean and free of waxes, sealers or finishes.
3. Surface temperature should be between: 50 °F to 80 °F (10 °C to 27 °C).
4. Allow new grout to cure before sealing (follow grout manufacturer's recommendations on cure time).
5. Protect surrounding surfaces by masking off areas not intended to be sealed.
6. Keep work area well ventilated while applying sealer.
7. Shake well before use.
8. Always test product in an inconspicuous area to ensure desired results.
9. Apply a liberal amount of sealer to the surface using a brush, paint pad, roller, or low pressure sprayer.
10. Allow sealer to penetrate stone surface for 15 minutes. Apply more sealer if surface begins to dry before 15 minutes have passed. DO NOT ALLOW SEALER TO DRY ON THE SURFACE.
11. After 15 minutes, remove all sealer that has not absorbed into the surface. Wipe surface completely dry using a clean dry cloth. If a residue appears, apply a light coat of sealer, agitate with a white nylon pad or brush, and dry the surface using a clean dry cloth.
12. Highly porous surfaces may require additional applications. Wait 30 minutes between applications. After final application wipe entire surface dry and clean sealing tools with water.

## Preventing Mortar & Polymeric Sand Haze

Porous stone and concrete pavers can be stained by mortar and polymeric sand during installation. Sealing stone and concrete pavers before installing mortar and / or polymeric sand will make clean up much easier. Apply sealer according to directions above. Wait a minimum of 2 hours before installing mortar or polymeric sand in joints.

## Satisfaction Guarantee

MORE™ Surface Care, LLC warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. MORE™ Surface Care's sole liability under this warranty shall be limited to replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with MORE™ Surface Care's printed instructions. MORE™ SURFACE CARE MAKES NO OTHER WARRANTIES EITHER EXPRESSED OR IMPLIED. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country and / or territory to another. This warranty is not transferrable.