



PREMIUM STONE ENHANCER

Premium Stone Enhancer

Description

A high performance, water-based, penetrating sealer that enhances stone's natural color, texture, and unique character. At the same time, the sealer provides maximum protection against oil and water-based stains. The right choice for the most demanding professionals and expert stone craftsmen.

Features

- Water Based
- Maximum Stain Protection
- No Gloss / Natural Look
- Enhance and Seal in One Easy Step
- Safe and Easy to Use
- Low Odor
- VOC Compliant
- Interior and Exterior
- Professional Grade

Recommended Surface Types

Natural stone, including granite, marble, slate, limestone, travertine, sandstone, Saltillo and other clay-based tile.

Coverage

Up to 1,000 sq. ft. per gallon for a single coat depending on surface type and texture.

Expected Wear

Up to 8 years.

Available Sizes

Pint, Quart, Gallon

Technical Information

Cure Time: 72 hours

Foot Traffic: 6 hours after final application

Emergency / First Aid Procedures

INGESTION: Do not induce vomiting - seek medical attention

EYES: Flush with water - seek medical attention

SKIN: Rinse with water - seek medical attention

INHALATION: Move to fresh air - seek medical attention

EMERGENCY HOT LINE: 800-222-1222

Contact Information

MORE™ Surface Care, LLC Palo Alto, CA

844-404-MORE (6673)

www.moresurfacecare.com

Storage and Handling

1. KEEP OUT OF REACH OF CHILDREN AND PETS
2. Store and use in a well ventilated area
3. Minimize exposure to vapors
4. Minimize contact with skin and eyes
5. Dispose of unused product in accordance with local laws and guidelines
6. DO NOT allow to freeze
7. DO NOT mix with other chemicals

Safety / Protective Wear

Eye goggles or safety glasses.

USE CHEMICAL-RESISTANT GLOVES (i.e., nitrile) when handling product. Use a respirator in confined areas.

Usage Instructions

1. Read entire label before using and use only as directed.
2. Surface should be dry, clean and free of waxes, sealers or finishes.
3. Surface temperature should be between: 50 °F to 80 °F (10 °C to 27 °C).
4. Allow new grout to cure before sealing (follow grout manufacturer's recommendations on cure time).
5. Protect surrounding surfaces by masking off areas not intended to be sealed.
6. Keep work area well ventilated while applying sealer.
7. Shake well before use.
8. Always test product in an inconspicuous area to ensure desired results.
9. Apply a liberal amount of sealer to the surface using a brush, paint pad, roller, or low pressure sprayer.
10. Allow sealer to penetrate stone surface for 15 minutes. Apply more sealer if surface begins to dry before 15 minutes have passed. DO NOT ALLOW SEALER TO DRY ON THE SURFACE.
11. After 15 minutes, remove all sealer that has not absorbed into the surface. Wipe surface completely dry using a clean dry cloth. If a residue appears, apply a light coat of sealer, agitate with a white nylon pad or brush, and dry the surface using a clean dry cloth.

Pre-Grout Sealing / Grout Release

Porous stone and tile can be stained by grout during installation. Sealing stone and tile before grouting will make grout clean up much easier. Apply sealer according to directions above. Wait a minimum of 2 hours before grouting.

Satisfaction Guarantee

MORE™ Surface Care, LLC warrants to the original purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. MORE™ Surface Care's sole liability under this warranty shall be limited to replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with MORE™ Surface Care's printed instructions. MORE™ SURFACE CARE MAKES NO OTHER WARRANTIES EITHER EXPRESSED OR IMPLIED. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country and / or territory to another. This warranty is not transferrable.