

#### Home of the Tiger hoisting, clamping, winching and height safety ranges



# **G80 Insulated Blank Swivel** Model No. 8-088N

### **Main Features**

- With ball bearing
- Design factor 4:1 proof tested and certified
- Individually tested to resist 1000 Volts insulated with Test Certificate
- Designed for the protection of overhead cranes during welding operations on suspended loads





YOKE G80 FITTINGS


#### **Certification**:

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC, the Supply of Machinery (Safety) Regulations 2008 and Section 6 of the Health and Safety at Work Etc Act 1974.

Manufactured and tested in accordance with EN1677-1. All YOKE Lifting points meet or exceed all the requirements of ASME B30.26.

Technical Data						
	Product Code	Capacity (tonne)	For Grade 80 Chain (mm)	Dimensions (mm)		Net Weight (kg)
				D	L	Net Weight (kg)
	8-088N-07	2.00	7, 8	50	75	0.6
	8-088N-10	3.15	10	62	94	1.2
	8-088N-13	5.30	13	77	123	2.4
	8-088N-16	8.00	16	94	143	4.2
	8-088N-20	12.50	18, 20	109	164	6.7

Tachnical Data



Due to our policy of continual product development, dimensions, weights and specifications may change without prior notice. Please check with your Tiger sales team when ordering.

## Our innovation, your safety