Kawasaki Versys Garmin Zumo® 450-550 GPS Mount Installation Instructions

<u>Items included</u>



Main Plate 2 Posts 2 Phillips Large Screws 4 Phillips Small Screws



From Garmin RAM kit: 4 M-4 Screws

4 Locknuts

Tools needed for installation



From your garage toolbox (from left to right):

- 8 mm (or 5/16") open wrench **or** adjustable wrench
- Phillips screwdriver

From your Kawasaki Versys toolkit (on the right):

• 4 mm hex wrench



To attach Garmin mount to our GPS Mount:

Phillips screwdriver 7 mm open wrench **or** adjustable wrench

<u>Installation Instructions</u>

Assemble the GPS Mount
 Lay down the Main Plate with the beveled edge of the plate down, and position the two posts as seen in the photo



2) Attach the posts to the main plate with the 4 small Phillips screws by putting the screws through the plate from the bottom side and screwing them into the posts



3) Align the Garmin Zumo mount to our GPS Mount, and insert the four screws and locknuts from your Garmin Zumo RAM kit as shown:



4) Tighten all the screws and locknuts with the screwdriver and the 7 mm open wrench (or adjustable wrench), as shown:



5) Plug in the Garmin Zumo power cable into the Garmin Zumo mount, as shown:



Don't forget to secure the connecting cable per Garmin instructions.

6) Remove 4 screws from the windscreen by using the 4 mm hex wrench and the 8 mm open wrench



7) Once the windscreen is removed, install the GPS Mount with the 2 large screws to the brackets of the windscreen (from behind).



- 8) Tighten all the screws (you may use Loctite ® for added security) and position the power cable to your liking
- 9) Reinstall the windscreen

10) Slide the Garmin Zumo GPS unit into its base



The installation is now complete.

You may adjust the position of the GPS Mount to mount higher on the windscreen bracket, if this is to your liking. The photos below show the alternative, higher mounting position:



Thank you for buying our product!