

ThruWall Depositories

Product: [Ease SingleDrop ThruWall](#)

Catalog#: [10-8100](#)

Specifications are subject to change without notice. Please see www.kingsley.com for the most current specifications. **Made in the USA.**

ThruWall System Construction/Features

Materials:	<ul style="list-style-type: none">• Exterior: Heavy-duty stainless steel faceplate, depository door flap, and built-in weather hood.• Interior: Aircraft grade aluminum body including 13-inch four-sided chute housing. AirBloc neoprene rubber panels.
Weather Resistance:	Equipped with MagnaClose technology that automatically closes the depository door after materials have passed through. Depository door is gravity and weight balanced to prevent the entry of rain or snow and stays closed in most winds.
Air Draft Prevention:	The AirBloc system helps to eliminate drafts caused when the depository door is opened. It helps stabilize outside air temperature before it enters the building.
Theft Deterrence:	The upward angle of the entry chute, length of the slide chute, and the AirBloc system prevent reaching inside through the depository door and block theft of materials with a claw apparatus.
Available Wording:	Vinyl decal, silkscreen, and routing available. See website for complete list of standard wording options.
Locking Method:	Depository door locks from the inside with rotating locking rod mechanism. Operated by an easy to use knob.
ADA Compliancy:	ADA compliant when properly installed.
Assembly Required:	The Ease SingleDrop is a pre-assembled, one piece unit so it is easy to install. The internal slide is a separate piece that must be hooked in separately once the depository is installed. This allows the internal slide to be adjusted in height if needed.
Compatibility:	Contingent on height of installation, the Ease SingleDrop is compatible with any Kingsley receiving cart. It is also compatible with most conveyer systems.

ThruWall Measurements

Overall Dimensions:	22- ¹ / ₂ " W x 16- ¹ / ₂ " D x 20- ¹ / ₂ " H [571.5 mm W x 419.1 mm D x 520.7 mm H]
Depository Opening:	17- ³ / ₄ " W x 2- ⁷ / ₈ " H [450.8 mm W x 73 mm H]
Product Weight:	17 lbs. [7.71 kg]
Shipping Method/Class:	Ground or freight/class 150

Installation

(Rough cut only. Please visit www.kingsley.com for complete instructions)

Rough Cut:	36- ¹ / ₂ " [927.10 mm] from exterior floor to bottom of cut out. Rough cut opening 20- ³ / ₁₆ " W x 18- ⁵ / ₁₆ " H [512.76 mm W x 465.1 mm H] all the way through wall. Four-sided chute housing extends 13 inches from the faceplate and will cover the wall rough cuts when installed.
Trim:	¹ / ₄ " [6.35 mm] trim on the top, bottom and sides of opening.

Accessories/Options for This System:

- Thick Wall Extension Kit** – #19-0001 (for walls 13-24" thick)
- Braille Tags** – Reads: BOOK DROP (#99-8100) or VIDEO DROP (#99-8105)
- Custom Wording** – Contact us for a quote.