

# ThruWall Depositories

Product: **Ease Drive-Up ThruWall**

Catalog#: **10-8175**

Specifications are subject to change without notice. Please see [www.kingsley.com](http://www.kingsley.com) for the most current specifications. **Made in the USA.**

---

## ThruWall System Construction/Features

---

<b>Materials:</b>	<ul style="list-style-type: none"><li>• <b>Exterior:</b> Heavy-duty stainless steel faceplate, depository door flap, and built-in weather hood.</li><li>• <b>Interior:</b> Aircraft grade aluminum body including 13-inch four-sided chute housing. AirBloc neoprene rubber panel.</li></ul>
<b>Weather Resistance:</b>	Depository door is gravity and weight balanced to prevent the entry of rain or snow and stays closed in most winds. Weather stripping on the inside edges of the faceplate provide further protection from inclement weather.
<b>Air Draft Prevention:</b>	The AirBloc system helps to eliminate drafts caused when the depository door is opened. Helps stabilize outside air temperature before it enters the building.
<b>Theft Deterrence:</b>	The upward angle of the entry chute and length of the slide chute prevent reaching inside through the depository door and block theft of materials with a claw apparatus.
<b>Available Wording:</b>	Vinyl decal and silkscreen available. See website for complete list of standard wording options.
<b>Locking Method:</b>	N/A
<b>ADA Compliancy:</b>	ADA compliant when properly installed.
<b>Assembly Required:</b>	The Ease Drive-up is a pre-assembled, one piece unit so it is easy to install. The internal slide is a separate piece that must be hooked into place once the depository is installed. This allows the internal slide to be adjusted in height if needed or replaced with a longer one in a wall extension kit.
<b>Compatibility:</b>	Contingent on height of installation, the Ease Drive-Up is compatible with any Kingsley receiving cart except for the divided DualDrop carts. It is also compatible with most conveyer systems.



---

## ThruWall Measurements

---

<b>Overall Dimensions:</b>	22" W x 25- <sup>1</sup> / <sub>8</sub> " D x 20" H [558.8 mm W x 638.17 mm D x 508 mm H]
<b>Depository Opening:</b>	18" W x 3- <sup>1</sup> / <sub>4</sub> " H [457.2 mm W x 82.6 mm H] Depository opening projects outward 10.5" [266.7 mm] to assist with easier deposit of materials from vehicles.
<b>Product Weight:</b>	22 lbs. [ 9.98 kg]
<b>Shipping Method/Class:</b>	Ground or freight/class 150

---

## Installation

(Rough cut only. Please visit [www.kingsley.com](http://www.kingsley.com) for complete instructions)

---

<b>Rough Cut:</b>	36- <sup>1</sup> / <sub>2</sub> " [927.10 mm] from exterior floor to bottom of cut out. Rough cut opening 20- <sup>3</sup> / <sub>16</sub> " W x 18- <sup>5</sup> / <sub>16</sub> " H [512.76 mm W x 465.1 mm H] all the way through wall.
<b>Trim:</b>	<sup>1</sup> / <sub>4</sub> " [6.35 mm] trim on the top, bottom and sides of opening on interior wall. Exterior wall does not need trim as the faceplate covers the rough cut.

---

## Accessories/Options for This System:

**Thick Wall Extension Kit** – #19-0003 (for walls 13-24" thick)

**Braille Tags** – Reads: BOOK DROP (#99-8100) or VIDEO DROP (#99-8105)

**Custom Wording** – Contact us for a quote.