



ThruWall Depositories

Product: Collection Point Ballot Return ThruWall

Catalog#: 12-8155

Specifications are subject to change without notice. Please see www.kingsley.com for the most current specifications. **Made in the USA.**

ThruWall System Construction/Features

Materials:	Heavy-duty stainless steel faceplate, depository door flap, and built-in weather hood.
Weather Resistance:	Depository door is gravity and weight balanced to prevent the entry of rain or snow and stays closed in most winds.
Theft Deterrence:	This unit design includes anti-phishing features. For example, an upward depository angle and long retrieval distances prevents someone from reaching inside and pulling materials out. We test all our units to make sure that nothing sitting in your collection cart will be able to be reached.
Available Wording:	Vinyl decal, silkscreen, and routing available. See website for complete list of standard wording options.
Locking Method:	Depository door locks from the inside with rotating a hand operated cam lock while the interior door locks with a keyed camlock.
ADA Compliancy:	ADA compliant when properly installed.
Assembly Required:	The Collection Point Ballot Return is a pre-assembled, one piece unit so it is easy to install. The internal slide is a separate piece that must be hooked into place once the depository is installed. This allows the unit to be installed with appropriate hardware that would be normally blocked by the slide.
Compatibility:	Contingent on height of installation, the Collection Point Ballot return is compatible with any Kingsley receiving cart except for the divided DualDrop carts. It is also compatible with most conveyer systems.

ThruWall Measurements

Overall Dimensions:	18- ⁹ / ₃₂ " D x 19- ¹ / ₂ " W x 20- ¹ / ₂ " H [464.1 mm D x 470 mm W x 520.7 mm H]
Depository Opening:	13- ¹ / ₈ " W x ¹ / ₂ " H [334 mm W x 12.7 mm H]
Product Weight:	25.3 lbs. [9.88 kg]
Shipping Method/Class:	Ground or freight/class 150

Installation

(Rough cut only. Please visit www.kingsley.com for complete instructions)

Rough Cut:	38-7/8" [987.5 mm] from exterior floor to bottom of cut out. Rough cut opening 14-1/2" W x 15-1/4" H [368.3 mm W x 362 mm H] all the way through wall. Four-sided chute housing extends 12.75 inches from the faceplate and will cover the wall rough cuts when installed.
Trim:	1/4" [6.35 mm] trim on the top, bottom and sides of opening.

Transport Carts Used with This System:

#32-9050 – Ballot Return Cart

Accessories/Options for This System:

Braille Tags – Reads: BALLOT RETURN (#99-8115)

Custom Wording – Contact us for a quote.