



DIMENSIONI E PESI DIMENSIONS AND WEIGHTS		
	LUNGHEZZA LENGHT mm	PESO WEIGHT kg
DIVER 75 M/T	420	10
DIVER 100 M/T	477	11.5
DIVER 150 M/T	544	13
DIVER 200 M/T	640	16.1

DIMENSIONI E PESI DIMENSIONS AND WEIGHTS		
	LUNGHEZZA LENGHT mm	PESO WEIGHT kg
DIVER 100 M/T HF	520	12.1
DIVER 150 M/T HF	580	13.5
DIVER 200 M/T HF	640	16



CARATTERISTICHE IDRAULICHE (50 Hz) HYDRAULIC PERFORMANCES (50 Hz)								
PORTATA Lt/min CAPACITY m <sup>3</sup> /h	10	20	30	40	50	60	70	80
	0.6	1.2	1.8	2.4	3	3.6	4.2	4.8
PREVALENZA MANOMETRICA TOTALE m.c.a. TOTAL MANOMETRIC HEAD m.w.c.								
DIVER 75	35	33	30	26	22	18	14	9
DIVER 100	50	45	41	35	30	25	18	11
DIVER 150	72	67	60	52	45	35	26	16
DIVER 200	96	90	85	70	60	47	35	21

MONOFASE SINGLE-PHASE 230 V - 50 Hz	P <sub>2</sub> output Kw (Hp)	I nom. rated AMP	cond. cap. µF	TRIFASE THREE-PHASE 400 V - 50 HZ	P <sub>2</sub> output Kw (Hp)	I nom. rated AMP
DIVER 75M	.55 (.75)	4.6	16	DIVER 75T	.55 (.75)	1.7
DIVER 100M	.75(1)	5.9	20	DIVER 100T	.75(1)	2.4
DIVER 150M	1.1 (1.5)	7.8	30	DIVER 150T	1.1 (1.5)	3.3
DIVER 200M	1.5 (2)	10.7	35	DIVER 200T	1.5 (2)	4.9

CARATTERISTICHE IDRAULICHE (50 Hz) HYDRAULIC PERFORMANCES (50 Hz)								
PORTATA Lt/min CAPACITY m <sup>3</sup> /h	25	50	75	100	125	150	175	200
	1.5	3	4.5	6	7.5	9	10.5	12
PREVALENZA MANOMETRICA TOTALE m.c.a. TOTAL MANOMETRIC HEAD m.w.c.								
DIVER 100 HF	28	26	24	22	20	16	13	10
DIVER 150 HF	40	38	35	32	28	24	20	15
DIVER 200 HF	55	51	48	44	39	34	28	20

MONOFASE SINGLE-PHASE 230 V - 50 Hz	P <sub>2</sub> output Kw (Hp)	I nom. rated AMP	cond. cap. µF	TRIFASE THREE-PHASE 400 V - 50 HZ	P <sub>2</sub> output Kw (Hp)	I nom. rated AMP
DIVER 100M HF	.75(1)	6.2	20	DIVER 100T HF	.75(1)	2.5
DIVER 150M HF	1.1 (1.5)	8.1	30	DIVER 150T HF	1.1 (1.5)	3.5
DIVER 200M HF	1.5 (2)	10.8	35	DIVER 200T HF	1.5 (2)	4.9