

MAGIS HERCULES PRO PREVIEW

Split type **heat pump with 235 litres DHW storage tank**

The most complete heat pump only solution which combines the advantages of having inside the same casing 235 litres DHW storage tank and the possibility to manage systems up to 3 zones.

- Pre-loaded refrigerant fluid R32
- High COP and EER values
- Heating temperature range 20 - 65 °C
- Cooling temperature range 5 - 25 °C
- External unit can be installed full outdoor
- Indoor unit can be installed inside only
- 45-liter buffer tank with hydraulic circuit breaker function as standard in the indoor casing unit
- Internal casing unit can contain 3 pumps (3 zones, 1 of which is standard) and option kits



Available in a single package **dismountable into two parts**



| Model | Hydronic unit dimensions (H x W x D) mm | External unit dimensions (H x W x D) mm |
|-------|-----------------------------------------|-----------------------------------------|
| 4 | 1970 x 650 x 913 | 638 x 880 x 364 |
| 6 | 1970 x 650 x 913 | 638 x 880 x 364 |
| 9 | 1970 x 650 x 913 | 940 x 1010 x 384 |

| Model | Code | Heating output kW | Cooling output kW | Power supply V | Refrigerant gas |
|----------------------|----------|-------------------|-------------------|----------------|-----------------|
| MAGIS HERCULES PRO 4 | 3.030428 | 4,4 | 5 | 230 | R32 |
| MAGIS HERCULES PRO 6 | 3.030429 | 6 | 6,5 | 230 | R32 |
| MAGIS HERCULES PRO 9 | 3.030430 | 9 | 8,7 | 230 | R32 |

Data referred to the following conditions: heating air/water temperature 7-6 °C / 30-35 °C
cooling air/water temperature 35-24 °C / 23-18 °C

