

## RETAIL ELECTRIC/CRAFT KILN/FURNACE

VALID FROM 29/03/2017

FRONT LOADER MODEL	INTERNAL W x D x H / mm	Ft <sup>3</sup>	L <sup>3</sup>	KG	Programmer Fittings (GST included)	SR92 (GST included)	STAFFORD (GST included)
<b>Small Kiln</b>							
K2 FL	230 x 230 x 230	.40	12	30	\$ 4,490	\$ 5,040	\$ 5,590
K4 FL	330 x 330 x 230	0.90	25	55	\$ 4,765	\$ 5,315	\$ 5,865
K4A FL	330 x 330 x 330	1.40	35	75	\$ 5,260	\$ 5,810	\$ 6,360
K6 FL	380 x 380 x 460	2.35	66	95	\$ 5,975	\$ 6,525	\$ 7,075
<b>Large Kiln</b>							
K7MW FL	460 x 460 x 460	3.40	97	175	\$ 8,516	\$ 9,066	\$ 9,616
K8 FL	460 x 460 x 686	5.06	145	380	\$ 9,913	\$ 10,463	\$ 11,013
K9 FL	460 x 460 x 915	6.80	193	460	\$ 11,189	\$ 11,739	\$ 12,289
K10 FL	610 x 610 x 610	8.00	226	440	\$ 11,717	\$ 12,267	\$ 12,817
K11A FL	610 x 610 x 760	10.00	283	500	\$ 12,135	\$ 12,685	\$ 13,235
K12 FL	610 x 610 x 915	12.00	340	520	\$ 14,247	\$ 14,797	\$ 15,347
K12A FL	610 x 610 x 1370	18.00	510	580	\$ 17,382	\$ 17,932	\$ 18,482
TOP LOADER MODEL	INTERNAL W x D x H / mm	Ft <sup>3</sup>	L <sup>3</sup>	KG	Programmer Fittings + GST	SR92 + GST	STAFFORD + GST
<b>Small Kiln</b>							
K5 TL	345 x 345 x 370	1.53	44	85	\$ 5,574	\$ 6,124	\$ 6,674
K6 TL	380 x 380 x 460	2.35	66	95	\$ 6,624	\$ 7,174	\$ 7,724
<b>Large Kiln</b>							
K7 TL	460 x 460 x 460	3.40	97	300	\$ 10,661	\$ 11,211	\$ 11,761
K8 TL	460 x 460 x 610	4.50	129	410	\$ 11,013	\$ 11,563	\$ 12,113
K9 TL	915 x 460 x 460	6.80	193	460	\$ 12,828	\$ 13,378	\$ 13,928
K10 TL	610 x 610 x 610	8.00	226	500	\$ 13,345	\$ 13,895	\$ 14,445
K11 TL	915 x 460 x 610	9.00	256	520	\$ 14,269	\$ 14,819	\$ 15,369
K12 TL	915 x 610 x 610	12.00	340	560	\$ 15,523	\$ 16,073	\$ 16,623



## **NOTE: ALL UNITS CONNECT WITH NEUTRAL**

MODEL	PHASE	VOLTS	AMPS	KW	TEMP°C
K2 FL	1	240	10	2.4	1200°C
K2 FL	1	240	15	3.6	1300°C
K4 FL	1	240	10	2.4	1200°C
K4 FL	1	240	15	3.6	1300°C
K4A FL	1	240	10	2.4	1200°C
K4A FL	1	240	15	3.6	1300°C
K5 TL	1	240	15	3.6	1300°C
K6 FL/TL	1	240	15	3.6	1300°C
K6 FL/TL	1	240	20	4.8	1300°C
K6 FL	1	240	25	6	1300°C
K6 TL	2	415	10	4.8	1300°C
K7 MW FL	1	240	20	4.8	1300°C
K7 MW FL	1	240	30	7.2	1300°C
K7 MW FL	2	415	15	7.2	1300°C
K7 MW FL	3	415	10	7.2	1300°C
K7 TL	3	415	10	7.2	1300°C
K8 TL	3	415	15	10.8	1300°C
K8B FL	3	415	15	10.8	1300°C
K9 FL/TL	3	415	20	14.4	1300°C
K10 FL/TL	3	415	23	16.5	1300°C
K11 TL	3	415	25	18	1300°C
K11A FL	3	415	25	18	1300°C
K12 FL/TL	3	415	28	20.16	1300°C
K12A FL	3	415	40	28.8	1300°C

**Please note: For extensive 1280°C/stoneware, we can supply K6 as 240V-25amp, for extended operating life of elements, requires direct wiring or 30 amp plug top and lead (not supplied).**

**It is recommended that circuit breakers or fuses are electrical cables are rated at a minimum of 20% above the required amperage of the unit.**

**Three phase kilns are 5 wire – 1 earth, 1 neutral, 3 actives.**

**Note: We can manufacture quite a number of 2 and 3 phase kilns as single phase if you have adequate single phase power available. The same may also be done with the multi-sided octagonal kilns.**