

## **SAFETY DATA SHEET**

Product Name Processed Clay (WET)

#### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name NORTHCOTE POTTERY SUPPLIES PTY LTD

Address 142-144 Weston Street, Brunswick East, VIC, AUSTRALIA, 3057

**Telephone** (03) 9387 3911 **Fax** (03) 9387 3911

Email <u>info@northcotepotterysupplies.com.au</u>

Synonym(s) PS3010 STONEWARE • RHB WHITE RAKU HANDBUILDING • WEB HANDBUILDING EARTHENWARE •

PS2000 TERRACOTTA

MSDS Date 1 Aug 2019

#### 2. HAZARDS IDENTIFICATION

# NOT CLASSIFIED AS HAZARDOUS ACCORDING TO ASCC CRITERIA

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. None Allocated DG Class None Allocated Subsidiary Risk(s) None Allocated Packing Group None Allocated Hazchem Code None Allocated EPG None Allocated

### 3. PHYSICAL DATA

**APPEARANCE:** Amorphous plastic substance when dry (fine powder)

**BOILING POINT:** Not applicable

**MELTING POINT:** Softening starts at approximately 1200oC

FLASH POINT: Non Flammable

#### 4. HEALTH HAZARD INFORMATION

**EYE CONTACT:** Irritation resulting from loss foreign bodies **SKIN (CONTACT):** Inert material. Mild skin irritation may occur

**INHALATION (BREATHING):** The dry dust from this moderately irritating to nose and throat

INGESTION (SWALLOWING): Non toxic. Vomiting or constipation may occur if sufficient quantity is swallowed

## Product Name Processed Clay (WET)

5. FIRST AID

**EYE CONTACT:** If in eyes, hold eyelids apart and flush the eye continuously with running water.

Continue flushing until advised to by the Poison Information Centre or a doctor, or for

at least 15 minutes

**SKIN (CONTACT):** Wash affected area with soap and water.

**INHALATION (BREATHING):** If inhaled, remove to fresh air. Rinse mouth with water and drink water to remove

dust from throat. Blow nose to clear.

INGESTION (SWALLOWING): Terminate exposure and seek medical advice. For advice, contact the Poison

Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed,

do not induce vomiting.

## 6. PRECAUTIONS FOR USE

**EXPOSURE LIMITS:** Threshold Limit Value (TLV) for respirable dust (from dried clay) is 5mg/m<sup>3</sup>

**VENTILATION:** Use a well ventilated area.

PERSONAL PROTECTION: Approved dust masks should be worn when dealing with dry clay but are not necessary

for wet clay handling.

Eye protection is not require under normal circumstances.

Wear normal work clothes.

**FLAMMABILITY:** Non Flammable.

#### 7. SAFE HANDLING INFORMATION

**STORAGE AND TRANSPORT:** Protect containers against physical damage.

SPILLS AND DISPOSAL: Avoid creating dust and preferably collect dust by vacuum cleaning or hose away with

excess water. Wet clay on floor surface can be a slipping hazard and should be cleaned up immediately. Dispose of as a non toxic waste. Recycle where possible by the end

user.

FIRE/EXPLOSION HAZARD: Non combustible.

**CONTACT POINT:** The Manager

Bendigo Pottery Australia

146 Midland Highway, Epsom, VIC 3551

Ph: (03) 5448 4404 Fax: (03) 5448 4873

Email: info@bendigopottery.com.au

**SDS Date**: 1 Aug 2019

-END OF SDS-