



Never compromise on quality!



2-PART WOOD FILLER

Permanently Repairs Wood



Description

A tough, durable, two part wood filler based on polyester resin. Long lasting repair for all wood types.

Benefits:

- ◆ Can be stained, painted, varnished or dyed once cured.
- ◆ Chemical curing system - sets hard in 30 minutes to any depth.
- ◆ Sandable in 30 minutes.
- ◆ High strength; can be drilled, nailed, planed and carved once dry.
- ◆ Good movement capabilities to flex with wood. No shrinking or cracking.
- ◆ Waterproof, suitable for internal and external application.

Uses

General wood filling of windowsills, frames, banisters, MDF and laminates, etc. Repairing wood damaged by wet rot in both internal and external locations. Repair damage and chips to parquet or laminate flooring, wooden furniture, etc.

Preparation

Ensure the repair area is clean and dry and free from dust or any contamination that may affect adhesion. Any rotten wood should be totally removed.

If you intend to overstain the repair, choose the filler colour closest to the wood you are filling, not the stain you intend to use. Always check the stain on a small area as the filler may absorb the stain at a different rate to the wood.

Application

Mix a golf ball volume of filler (approx. 38mm diameter and a 38mm strip of hardener into a homogeneous paste with the spatula provided. Press firmly into the surface to be repaired, leaving it slightly proud. Leave to dry for about 30 minutes until hard before finishing (sanding and or painting/staining).

Limitations

Do not attempt to push mixture back into pack once mixed. Avoid contact with eyes and skin. Always test a small inconspicuous area for colour matching purposes.

Throw away any unused mixed material after 10 minutes.

Size

275ml

Colours

Pine, white, light oak, dark oak and teak.

Storage Conditions

Store upright between 10-20°C in cool dry conditions away from sources of ignition. Keep containers sealed.

Shelf Life

2 years from date of manufacture when stored as above.

Disposal of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

Base	2 Part system: Polyester resin with Benzyl Peroxide Hardener
Flammability	Flammable
Consistency	Thick Paste
Open Time	10 minutes maximum
Specific Gravity	ca. 1.10
Shrinkage	Nil at all depth
Working Temperature	+5°C to +30°C. (Optimum 20°C).
Temperature Resistance	-20°C to +100°C.

Container Sizes

Code:	BDWF2PN	BDWF2WH	BDWF2LO
Size:	275ml	275ml	275ml
Colour:	Pine	White	Light Oak
Barcode:	5060021371485	5060021371478	5060021371492

Code:	BDWF2DO	BDWF2TK
Size:	275ml	275ml
Colour:	Dark Oak	Teak
Barcode:	5060021371874	5060021371881

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number: 6152
ISO 9001
ISO 14001



BOND IT
Unit G16 River Bank Way, Lowfields Business Park,
Elland, West Yorkshire HX5 9DN.
Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
Email: sales@bond-it.co.uk Website: www.bond-it.co.uk



V2 23/11/16
Supersedes V1 10/2/16