
5X5 BASEBALL/SOFTBALL NET ASSEMBLY INSTRUCTIONS

Our video instructions provide the best guidance for setting up your 5x5 Baseball/Softball Net. They can be viewed online at




RukketSports

Please call us if you have any questions or concerns at **1-855-4RUKKET** Please read our product safety warnings before setup




1. Join the two slightly bent pipes together (Fig. A) Then attach both end legs (Fig. B)




4. Pull the other fiberglass rod inward to thread the other sleeve over it. Then attach the white cord.



7. Hook the elastic loops from the strike zone onto the posts at the base of the frame.



2. Assemble both black fiberglass rods and insert them into the metal base.



5. Hook the lower elastic loops around the posts at the base of the frame.



8. To adjust the height of the strike zone target, slide the plastic adjusters on the nylon tape up or down



3. Thread one sleeve over a fiberglass rod and loop the white cord over the top of the rod.



6. Connect the black hooks at the top of the strike zone to the red loops in the upper corners of the net.

!! WARNING !!

Please use adult supervision and follow the instructions when setting up and using the net.
Regular use or abuse will eventually strain the netting and may break it.

- Do not stand behind the net.
- This net is not intended for personal protection.

- This net deflects fast moving objects, so people should be at least ten (10) feet away.

PRIOR TO USE

 Inspect the netting and frame for damage or wear.
 Make sure the frame and net are assembled correctly and on a fla surface, at least ten (10) feet from structures and vehicles.

- The user should be positioned directly in front of the net.

- Failure to follow these precautions could result in serious injury or damage to property.

QUESTIONS? GIVE US A CALL! (1-855)-478-5538

