

SpeedWash™



Power Washers



3200 psi - Model G0089120 (50-State & Canada) UPC: 696471099669



Included Attachments:





FEATURES

ERGONOMIC SPRAY GUN WITH PowerDial™

- Four application settings for optimal cleaning performance
 —car, wood deck, concrete, soap
- Inverted trigger with cushion grip for extended use

POWERFUL GENERAC OHV ENGINE

Delivers maximum cleaning performance and reliability

MAINTENANCE FREE PUMP WITH EASY-ACCESS HOSE CONNECTIONS

Prevents kneeling down on the ground

TIME SAVING ATTACHMENTS

- Power Broom
- Turbo Nozzle
- Soap Blaster

30' FLEXIBLE HOSE

- Non-kinking
- Non-marring
- Abrasion Resistant

2 of 2

GENERAC®

3200 psi specifications

PRESSURE AND FLOW

Outlet Pressure (psi/bar)	3200/221
Flow Rate (gpm)/(L/min)	2.7/10.2

ENGINE

Manufacturer	Generac
Displacement (in ³ /cc)	12.9/212
Туре	OHV (Overhead Valve)
Orientation	Horizontal
Low Oil Shutdown System	No
Fuel Capacity (gal/L)	0.87/3.3
Fuel On/Off Switch	Yes
Oil Capacity (oz/L)	16.6/0.49
Lubrication Method	Splash
Recommended Engine Oil	10W-30/SAE 30
Throttle Control	Fixed Speed
Choke	Manual
Starting Method	Recoil Pull Start

PUMP

Туре	Axial Cam
Material	Aluminum
Maximum Water Supply Temperature (°F/°C)	100/38

HOSE

Туре	Polyurethane
Length (ft/m)	30/9.1
Diameter (in/mm)	0.25/6.4
Rating (psi/bar)	3200/220
Connectors	M22 Threaded

DETERGENT SYSTEM

Chemical Tank	Yes
Chemical Tank Size (gal/L)	0.5/1.9

NOZZLES

Nozzle Descriptions	0°, 25°, 40°, Soap, Soap Blaster,
	Turbo, and Power Broom

GUN & LANCE

Gun Type	PowerDial™
Gun to Lance Connection	M22 Threaded
Gun to Hose Connection	M22 Threaded
Lance Length (in/cm)	21/53.3
Lance to Nozzle Connection	Quick Connect

FRAME & MISC.

Handle	Fixed - Click In
Frame Construction	Steel
Wheels - Never Flat (in/cm)	1.75 x 10/4.4 x 25.4

DIMENSIONS & WEIGHTS

25.7/65.2
18.9/47.9
34/86.3
62/28.3
24/61
20.1/51
22.8/58
71/32

WARRANTY

Warranty	3 year limited

