

Automatic Transfer Switches

Limited Circuit Automatic Transfer Switch



100 Amp, Single Phase, 16 Space, NEMA 3R
Model: RXG16EZA3



Description

This Generac automatic transfer switch is designed to operate with air-cooled generators. This transfer switch has an integrated load center to allow for essential circuit backup. It is especially useful where the main service is large, and only a portion of the building will be served by the generator, or when the main electrical breaker panel is located outdoors. It comes standard with a 16 space breaker panel that can be populated with the appropriate sized breakers needed for any application. This transfer switch is ETL listed. This switch is listed for use with Siemens®, Eaton®, or Square D® one inch breakers. The bottom four breaker spaces will accommodate tandem breakers, making the panel expandable to 24 circuits.

Standard Features

This automatic transfer switch is housed in an all-weather, aluminum NEMA 3R enclosure with electrostatically applied and baked powder paint. The Heavy Duty Generac Contactor is a ETL recognized device, designed for years of service. The controller on the generator handles all of the timing, sensing and exercise functions. Multi listed for use with 1" standard, tandem, GFCI and AFCI breakers from Siemens, Eaton, and Square D for the most flexible and cost-effective installation. All switches are covered by a 5 year limited warranty.

Contactors Rating

The automatic transfer switch contactor is rated at 250 VAC and is available in a single phase configuration only.

100 Amp, Single Phase, 16 Space

Limited Circuit Automatic Transfer Switches

Functions

All timing and sensing functions originate in the generator controller.

Utility Voltage Drop-out	<60%
Timer to Generator Start	10 Second Factory Set, Adjustable Between 2 - 1,500 Seconds by a Qualified Dealer*
Engine Warmup Delay	5 Seconds
Standby Voltage Sensor	60% for 5 Seconds
Utility Voltage Pickup	>80%
Re-transfer Time Delay	15 Seconds
Engine Cooldown Timer	60 Seconds
Exerciser	Nexus™: 12 Minutes Weekly Evolution™: 5 to 12 Minutes Adjustable, Weekly/Bi-weekly/Monthly
Auxiliary Lock Out Contact	Lock Out a Single Load or Annunciate Generator Transfer Status
The Transfer Switch can be Operated Manually Without Power Applied	

* When used in conjunction with units utilizing Evolution™ controls

Specifications

Model	RXG16EZA3
Amps	100
Voltage	120/240, 1Ø
Load Transition Type (Automatic)	Open Transition
Enclosure Type	NEMA 3R
Compliance	cETLus
Withstand Rating (Amps)	10,000
Lug Range	1/0 - #14
UPC Code	696471069907
Tandem Breaker Capabilities	8 Tandems

Dimensions

Model		RXG16EZA3
Height (in / cm)	H1	26.8 / 68.1
	H2	30.1 / 76.5
Width (in / cm)	W1	10.5 / 26.7
	W2	13.5 / 34.3
Depth (in / cm)		6.9 / 17.5
Weight (lb / kg)		39 / 17.69

