

## Front Tine Tiller

## Residential Power Tools

1 of 2

Model: TW15221GMNG (50-State)  
UPC: 843530007602



## FEATURES

- **Adjustable tilling width:** Choose between 11 in (27.9 cm), 16 in (40.6 cm), or 21 in (53.3 cm) tilling widths to prepare larger gardens or to cultivate between rows.
- **Powerful OHV Generac engine:** Easy-starting 98cc OHV Generac engine provides 3.33 ft-lbs (4.5 Nm) of gross torque.
- **Easy maneuverability:** 8 in (20.3 cm) never-flat wheels are lightweight and make transport hassle free.
- **Adjustable depth drag stake:** Drag stake adjusts easily to optimize tiling in different soil types.
- **Simple operation:** Single lever operation makes tilling simple and straight forward.

## Front Tine Tiller

## Specifications

## Specifications

Engine	
Displacement	98cc
Torque	3.33 ft-lbs (4.5 Nm)
Starting	Manual
Engine speed	3,600 rpm
Bore x stroke	56 mm x 40 mm
Compression ratio	8.5 : 1
Spark plug	Torch E6TC/E6RTC, Champion RN9YC, NGK BPR6ES, Bosch WR6DC
<b>Construction</b>	
Tines	Powder coated steel
Frame	Powder coated steel
Handlebars	Powder coated steel
<b>Tilling Details</b>	
Tilling width	11 in, 16 in, or 21 in (27.9 cm, 40.6, or 53.3 cm)
Tilling depth	7–11 in (18–28 cm)
Tine speed	180 rpm

Unit Dimensions	
Height	40 in (102 cm)
Width	24 in (61 cm)
Length	48 in (122 cm)
Wheels	8 in (20.3 cm)
Unit weight	95 lbs (43.1 kg)
<b>Packaging</b>	
Packaging dimensions (in / cm)	28 x 18 x 26 / 71.1 x 45.7 x 66.0
Packaging weight (lbs / kg)	105 / 47.6
<b>Miscellaneous</b>	
Assembly time required	20 minutes
Controls	Throttle control, tine engage lever, ON/OFF switch, fuel shutoff
Personal protective equipment required	Eye protection, ear protection
USDA Certified spark arrestor	Yes
Warranty	2 year limited