

Pivoting. 1/8" Steel thick, 21-1/4" wide

37.5"

## Yardbeast 3514 Specifications

Front Axle:

Hand tow bar length

last update 11/16 Chipper 3.5" Chipping capacity: Rotor RPM: 3,000 Rotor Weight: 56 lbs. Blade: D2 Tool Steel Blade 5.82" x 2.33" Blade dimensions: 7/16" wafer front disc with 1/4" rotor vanes Rotor Construction 17.32" Flywheel: Feed Hopper: 24" x 11" Frame construction: 7-ga steel. Weld seams all around Bearing units: SKF® roller sealed bearings /custom steel housing Discharge height: 54.7" Control: Discharge deflector Chipper Weight (w/engine): 320 lbs **Engine** Make: Kohler CH440 Command Pro® 14HP engine RPM: 3,600 Torque: 19.8ft-lb @ 2,400RPM Dry Weight: 72.8 Lbs Displacement: 429 cc Oil Capacity 1.4 quarts (1.3 Lts) **Fuel Capacity** 7.0 Lts **Emissions** CARB Tier III certified **Transmission:** Drive: NORAM® Heavy Duty centrifugal clutch Belts 2- Gates® Hi-Power II B64 Belts Rotor Pulley: Cast Iron 2-groove pulley with 1-3/8" taper hub Trailer: Wheels: 4 - 10" Dia. Pneumatic Wheels Frame construciont: 1/8" thick steel with engine base tension plate Guards: Belt Guard with 3-point support Fixed, 1/8" Steel thick 21-1/4" wide Rear Axle: