

Yardbeast 4521 Specifications

Trailer:

last update 1/17 Chipper Chipping capacity: 4.5" Rotor RPM: 3,046 Rotor Weight: 85 lbs Dual A8 Tool Steel Reversible Blade Blade: 7" x 3" x 3/8" Blade dimensions: Rotor Construction 1" thick steel with 3/8" rotor vanes Flywheel: 21-1/4" 30" x 20" Feed Hopper: 3/16" thick steel. Weld seams all around Frame construction: Bearing units: SKF® roller sealed bearings /custom steel housing Discharge height: 72" Control: Discharge deflector Chipper Weight (w/engine): 860 lbs. **Engine** Make: Kohler CH640 Command Pro® 20.5HP engine RPM: 3,600 35.7t-lb @ Peak Torque Torque: Dry Weight: 90 lbs. Displacement: 674cc Oil Capacity 2 quarts (1.9 Lts) **Fuel Tank Capacity** 6.0 Gal w/ Carbon Vapor Canister CARB Approved **Emissions** CARB Tier III certified **Transmission:** Drive: NORAM® Heavy Duty centrifugal clutch Belts 2- Gates® Hi-Power II B63 Belts Rotor Pulley: Cast Iron 2-groove pulley with 1-3/8" taper hub Trailer: Wheels: 20.5" High Speed Wheel - 4 spoke 1/8" thick steel with engine base tension plate, and structural crosslinks Frame construcion: Total Frame width: 68" Suspension: Tor-Flex Suspension Guards: Belt Guard with 3-point support Rear Axle: Fixed, 1/8" Steel thick 21-1/4" wide Hitch:

1-7/8" Ball Hitch Coupler with chain hooks

DOT Compliant Trailer with suspension with lightning kit